

FEATURES

- ▶ Fully Encapsulated Plastic Case for PCB, Chassis and DIN-Rail Mounting Version
- ▶ Universal Input 85~264VAC, 47~440Hz
- ▶ I/O Isolation 4000VAC with Reinforced Insulation
- ▶ Operating Ambient Temp. Range -40°C to +80°C
- ▶ Overload/Voltage and Short Circuit Protection
- ▶ EMI Emission EN 55011/32 Class B Approved
- ▶ EMC Immunity EN 61000-4-2,3,4,5,6,8,11 Approved
- ▶ Medical EMC Standard with 4th Edition of EMI EN 55011 & EMS EN 60601-1-2 Approved
- ▶ Medical Safety with 2xMOPP per 3rd Edition of IEC/EN 60601-1 & ANSI/AAMI ES 60601-1 Approved
- ▶ UL508 Safety Approval Specifically for Industrial Application
- ▶ UL/cUL/IEC/EN 62368-1(60950-1) Safety Approval & CE Marking



PRODUCT OVERVIEW

The new MINMAX AYM-60 series is a range of fully encapsulated AC-DC power modules. These high performance products feature an extended operating temperature range of -40°C to +80°C. Universal input voltage 85-264VAC and UL/IEC/EN safety approvals including medical safety and UL 508 listing qualify these power supplies modules for applications in products with worldwide markets. EMI Emission EN 55011/32 Class B Approved. The AYM-60 series power modules provide a perfect solution for many space critical applications in commercial, medical and industrial electronic equipment.

Model Selection Guide

Model Number	Output Voltage	Output Current	Input Current		Max. capacitive Load	Efficiency (typ.)
			115VAC, 60Hz	230VAC, 50Hz		
			@Max. Load			
	VDC	mA	mA (typ.)		μF	%
AYM-60S051	5.1	10000	880	528	8000	84
AYM-60S12	12	5000	1000	600	3900	87
AYM-60S15	15	4000	1000	600	3300	87
AYM-60S24	24	2500	1000	600	1500	87
AYM-60S48	48	1250	988	593	680	88

Input Specifications

Parameter	Conditions / Model	Min.	Typ.	Max.	Unit
AC Voltage Input Range	All Models	85	---	264	VAC
Input Frequency Range		47	---	440	Hz
DC Voltage Input Range		120	---	370	VDC
No-Load Power Consumption		---	---	0.5	W
Inrush Current (Cold Start at 25°C)	115VAC	---	---	30	A
	230VAC	---	---	60	A

Output Specifications						
Parameter	Conditions / Model	Min.	Typ.	Max.	Unit	
Output Voltage Setting Accuracy		---	±1.0	±2.0	%Vnom.	
Line Regulation	Vin=Min. to Max. @Full Load	---	±0.2	±1.0	%	
Load Regulation	Io=0% to 100%	---	±0.5	±1.0	%	
Minimum Load	No minimum Load Requirement					
Ripple & Noise ₍₃₎	0-20 MHz Bandwidth	5.1VDC Output Models	---	2.0	3.0	%V _{PP} of Vo
		Other Output Models	---	1.0	1.5	%V _{PP} of Vo
Over Voltage Protection	Zener diode clamp	---	120	---	% of Vo	
Temperature Coefficient		---	±0.02	---	%/°C	
Overshoot		---	---	5	%	
Over Load Protection	85VAC, Hiccup Mode, auto-recovery	105	---	---	%Inom.	
	(long term overload condition may cause damage)					
Short Circuit Protection	Hiccup mode, Automatic Recovery					

General Specifications					
Parameter	Conditions	Min.	Typ.	Max.	Unit
I/O Isolation Voltage	Reinforced Insulation, Rated For 60 Seconds	4000	---	---	VAC
Leakage Current		---	80	---	µA
I/O Isolation Resistance	500 VDC	1000	---	---	MΩ
Switching Frequency		---	65	---	kHz
Hold-up Time	115VAC, 60Hz	---	20	---	ms
	230VAC, 50Hz	---	80	---	ms
MTBF (calculated)	MIL-HDBK-217F@25°C, Ground Benign	125,000			Hours
Safety Standards	UL/cUL 60950-1, CSA C22.2 No 60950-1				
	ANSI/AAMI ES60601-1, CAN/CSA-C22.2 No. 60601-1				
	IEC/EN 60950-1, IEC/EN 60601-1 3 rd Edition 2xMOPP				
	UL508, CSA C22.2 No.107.1-01				
Safety Approvals	UL/cUL 60950-1 recognition (UL certificate), IEC/EN 60950-1 (CB-report), UL/cUL 508 listed certificate				
	UL/cUL 62368-1 recognition (UL certificate), IEC/EN 62368-1 (CB-report)				
	ANSI/AAMI ES60601-1 2xMOPP recognition (UL certificate), IEC/EN 60601-1 3 rd Edition (CB-report)				

EMC Specifications					
Parameter	Standards & Level			Performance	
EMI	Conduction	EN 55011, EN 55032, EN 61000-6-4,		Without external components	Class B
	Radiation	EN 61000-6-3			
EMS	EN 60601-1-2 4 th , EN 55024, EN 61000-6-2, EN 61000-6-1				
	ESD	EN 61000-4-2 Air ± 15kV, Contact ± 8kV			A
	Radiated immunity	EN 61000-4-3 10V/m			A
	Fast transient	EN 61000-4-4 ±2kV			A
	Surge	EN 61000-4-5 ±1kV			A
	Conducted immunity	EN 61000-4-6 10Vrms			A
	PFMF	EN 61000-4-8 30A/m			A
	Dips & Interruptions	EN 61000-4-11	0% of 230VAC	0.5 cycle	A
			0% of 230VAC	1 cycle	A
70% of 230VAC			25/30 cycle	A	
0% of 230VAC			250/300 cycle	B	


Environmental Specifications

Parameter	Conditions	Min.	Max.	Unit
Operating Ambient Temperature Range		-40	+80	°C
Power Derating	Above +60°C	2.3		W / °C
Storage Temperature Range		-40	+95	°C
Humidity (non condensing)		---	95	% rel. H
Lead Temperature (1.5mm from case for 10Sec.)		---	260	°C

Notes


- This product is not designed for use in critical life support systems, equipment used in hazardous environment, nuclear control systems or other such applications which necessitate specific safety and regulatory standards other the ones listed in this datasheet.**
- Specifications typical at Ta=+25°C, resistive load, 115VAC, 60Hz input voltage, after warm-up time rated output current unless otherwise noted.
- Ripple & Noise of PCB mounting type measured with a 0.1µF/50V MLCC and a 1µF/50V Aluminum electrolytic.
- Safety approvals cover frequency 47-63 Hz.
- We recommend to protect the converter by a slow blow fuse in the input supply line.
- Other input and output voltage may be available, please contact MINMAX.
- Specifications are subject to change without notice.

Package Specifications PCB Mounting

Mechanical Dimensions		Pin Connections											
		<table border="1"> <thead> <tr> <th>Pin</th> <th>Function</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>AC (N)</td> </tr> <tr> <td>2</td> <td>AC (L)</td> </tr> <tr> <td>4</td> <td>+Vout</td> </tr> <tr> <td>6</td> <td>-Vout</td> </tr> </tbody> </table>		Pin	Function	1	AC (N)	2	AC (L)	4	+Vout	6	-Vout
Pin	Function												
1	AC (N)												
2	AC (L)												
4	+Vout												
6	-Vout												
<p>▶ All dimensions in mm (inches)</p> <p>▶ Tolerance: ±1.0 (±0.04)</p> <p>▶ Pin pitch tolerance: ±0.25 (±0.01)</p> <p>▶ Pin diameter \varnothing 1.0 ±0.1 (0.04±0.004)</p>													

Physical Characteristics

Case Size	: 88.9x67.5x34.2mm (3.50x2.66x1.35 inches)
Case Material	: Plastic resin (flammability to UL 94V-0 rated)
Pin Material	: Copper Alloy with Tin Plate Over Nickel Subplate
Weight	: 360g

Package Specifications Chassis Mounting (order code suffix C)
Mechanical Dimensions

Connections

Pin	Function
1	AC (N)
2	AC (L)
3	NC
4	+Vout
5	NC
6	-Vout
7	NC

NC: No Connection

▶ All dimensions in mm (inches)


 ▶ Tolerance: ± 1.0 (± 0.04)

Physical Characteristics

Case Size : 112.0x67.8x38.0mm (4.41x2.67x1.50 inches)

Case Material : Plastic resin (flammability to UL 94V-0 rated)

Weight : 380g

Package Specifications with DIN Rail Mounting Bracket
Mechanical Dimensions

Physical Characteristics

Case Size : 112.0x67.8x38.0mm (4.41x2.67x1.50 inches)

Case Material : Plastic resin (flammability to UL 94V-0 rated)

Weight : 433g

DIN-Rail Mounting Bracket (Order Code for Kit : AC-DIN-02)

Order Code Table

PCB Mounting	Chassis Mounting	With DIN Rail Mounting by two Order Code	
AYM-60S051	AYM-60S051C	AYM-60S051C	AC-DIN-02
AYM-60S12	AYM-60S12C	AYM-60S12C	AC-DIN-02
AYM-60S15	AYM-60S15C	AYM-60S15C	AC-DIN-02
AYM-60S24	AYM-60S24C	AYM-60S24C	AC-DIN-02
AYM-60S48	AYM-60S48C	AYM-60S48C	AC-DIN-02