



MAU300 Series  
Electric Characteristic Note

# MAU300 Series EC Note

DC-DC CONVERTER 2W, SIP Package

## Features

- ▶ Industrial Standard SIP-7 Package
- ▶ I/O Isolation 1000 VDC
- ▶ Operating Ambient Temp. Range -40°C to +85°C



## Applications

- ▶ Distributed power architectures
- ▶ Workstations
- ▶ Computer equipment
- ▶ Communications equipment

## Product Overview

The MINMAX MAU300 series is a range of 2W DC-DC converters in a small SIP Package featuring an I/O-isolation of 1000VDC. An excellent efficiency allows an operating temperature range of -40°C to +85°C.

These converters offer an economical solution for many applications where a voltage has to be isolated i.e for noise reduction, ground loop elimination, digital interfaces or for board level power distribution with isolated voltages.

## Table of contents

Model Selection Guide.....	P2	Recommended Pad Layout for Single & Dual Output Converter.....	P26
Input Specifications.....	P2	Test Setup.....	P27
Output Specifications.....	P2	Technical Notes.....	P27
Output Voltage Tolerance.....	P3	Packaging Information.....	P28
General Specifications.....	P3	Wave Soldering Considerations.....	P28
Environmental Specifications.....	P4	Hand Welding Parameter.....	P28
Characteristic Curves.....	P5	Part Number Structure.....	P29
Package Specifications.....	P26	MTBF and Reliability.....	P29

Model Number	Input Voltage (Range)	Output Voltage	Output Current		Input Current		Load Regulation	Max. capacitive Load	Efficiency (typ.)
			Max.	Min.	@Max. Load	@No Load			@Max. Load
			VDC	VDC	mA	mA	mA(typ.)	mA(typ.)	% (max.)
MAU301	5 (4.5 ~ 5.5)	3.3	500	10	452	60	11	470	73
MAU302		5	400	8	526		11		76
MAU303		12	165	3	495		7		80
MAU304		15	133	2.5	499		7	390#	80
MAU305		±5	±200	±4	519		10		77
MAU306		±12	±83	±1.5	504		7		79
MAU307		±15	±66	±1	501		7		79
MAU311	12 (10.8 ~ 13.2)	3.3	500	10	185	30	8	470	74
MAU312		5	400	8	212		8		78
MAU313		12	165	3	200		5		82
MAU314		15	133	2.5	200		5	390#	83
MAU315		±5	±200	±4	210		8		79
MAU316		±12	±83	±1.5	201		5		82
MAU317		±15	±66	±1	200		5		82
MAU321	24 (21.6 ~ 26.4)	3.3	500	10	92	15	8	470	74
MAU322		5	400	8	108		8		77
MAU323		12	165	3	101		5		81
MAU324		15	133	2.5	101		5	390#	82
MAU325		±5	±200	±4	105		8		79
MAU326		±12	±83	±1.5	102		5		81
MAU327		±15	±66	±1	100		5		82

\* Min. Output Current for Lower Load Regulation



# For each output

**Input Specifications**

Parameter	Model	Min.	Typ.	Max.	Unit
Input Voltage Range	5V Input Models	4.5	5	5.5	VDC
	12V Input Models	10.8	12	13.2	
	24V Input Models	21.6	24	26.4	
Input Surge Voltage (1 sec. max.)	5V Input Models	-0.7	---	9	
	12V Input Models	-0.7	---	18	
	24V Input Models	-0.7	---	30	
Input Filter	All Models	Internal Pi Type			





**Output Specifications**

Parameter	Conditions	Min.	Typ.	Max.	Unit
Output Voltage Accuracy		---	±1.0	±3.0	%Vnom.
Output Voltage Balance	Dual Output, Balanced Loads	---	±0.1	±1.0	%
Line Regulation	For Vin Change of 1%	---	±1.2	±1.5	%
Load Regulation	I <sub>O</sub> =20% to 100%	See Model Selection Guide			
Ripple & Noise	0-20 MHz Bandwidth	---	100	150	mV <sub>P-P</sub>
Temperature Coefficient		---	±0.01	±0.02	%/ <sup>o</sup> C
Short Circuit Protection		0.5 Second Max., Automatic Recovery			

**Output Voltage Tolerance**

MAU301 &amp; MAU302 Output Voltage VS Output Load Current

MAU305 Output Voltage VS Output Load Current

MAU311, MAU312, MAU315, MAU321, MAU322, MAU325  
Output Voltage VS Output Load CurrentMAU303, MAU304, MAU306, MAU307  
Output Voltage VS Output Load CurrentMAU313, MAU314, MAU316, MAU317, MAU323, MAU324, MAU326, MAU327  
Output Voltage VS Output Load Current

Output Voltage VS Input Voltage Range

**General Specifications**

Parameter	Conditions	Min.	Typ.	Max.	Unit
I/O Isolation Voltage	60 Seconds	1000	---	---	VDC
	1 Second	1200	---	---	VDC
I/O Isolation Resistance	500 VDC	1000	---	---	MΩ
I/O Isolation Capacitance	100kHz, 1V	---	80	120	pF
Switching Frequency		50	80	100	kHz
MTBF (calculated)	MIL-HDBK-217F@25°C, Ground Benign	2,000,000			Hours

**Environmental Specifications**


Parameter	Min.	Max.	Unit
Operating Ambient Temperature Range (See Power Derating Curve)	-40	+85	°C
Case Temperature	---	+105	°C
Storage Temperature Range	-50	+125	°C
Humidity (non condensing)	---	95	% rel. H
Lead Temperature (1.5mm from case for 10Sec.)	---	260	°C

**Notes**


- 1 Specifications typical at  $T_a=+25^{\circ}\text{C}$ , resistive load, nominal input voltage and rated output current unless otherwise noted.
- 2 These power converters require a minimum output loading to maintain specified regulation, operation under no-load conditions will not damage these modules; however they may not meet all specifications listed.
- 3 We recommend to protect the converter by a slow blow fuse in the input supply line.
- 4 Other input and output voltage may be available, please contact MINMAX.
- 5 Specifications are subject to change without notice.
- 6 The repeated high voltage isolation testing of the converter can degrade isolation capability, to a lesser or greater degree depending on materials, construction, environment and reflow solder process. Any material is susceptible to eventual chemical degradation when subject to very high applied voltages thus implying that the number of tests should be strictly limited. We therefore strongly advise against repeated high voltage isolation testing, but if it is absolutely required, that the voltage be reduced by 20% from specified test voltage. Furthermore, the high voltage isolation capability after reflow solder process should be evaluated as it is applied on system.

## Characteristic Curves


All test conditions are at 25°C. The figures are identical for MAU301




Efficiency Versus Output Current




Efficiency Versus Input Voltage  
Full Load




Output Voltage Versus Output Current



Typical Output Ripple and Noise  
 $V_{in}=V_{in\ nom}$ ; Full Load




Typical Input Start-Up and Output Rise Characteristic  
 $V_{in}=V_{in\ nom}$ ; Full Load




Derating Output Current Versus Ambient Temperature and Airflow  
 $V_{in}=V_{in\ nom}$

## Characteristic Curves


All test conditions are at 25°C. The figures are identical for MAU302




Efficiency Versus Output Current



Efficiency Versus Input Voltage  
Full Load




Output Voltage Versus Output Current



Typical Output Ripple and Noise  
 $V_{in}=V_{in\ nom}$ ; Full Load




Typical Input Start-Up and Output Rise Characteristic  
 $V_{in}=V_{in\ nom}$ ; Full Load




Derating Output Current Versus Ambient Temperature and Airflow  
 $V_{in}=V_{in\ nom}$

## Characteristic Curves


All test conditions are at 25°C. The figures are identical for MAU303




Efficiency Versus Output Current




Efficiency Versus Input Voltage  
Full Load




Output Voltage Versus Output Current



Typical Output Ripple and Noise  
 $V_{in}=V_{in\ nom}$ ; Full Load




Typical Input Start-Up and Output Rise Characteristic  
 $V_{in}=V_{in\ nom}$ ; Full Load




Derating Output Current Versus Ambient Temperature and Airflow  
 $V_{in}=V_{in\ nom}$

## Characteristic Curves


All test conditions are at 25°C. The figures are identical for MAU304




Efficiency Versus Output Current




Efficiency Versus Input Voltage  
Full Load




Output Voltage Versus Output Current



Typical Output Ripple and Noise  
 $V_{in}=V_{in\ nom}$ ; Full Load




Typical Input Start-Up and Output Rise Characteristic  
 $V_{in}=V_{in\ nom}$ ; Full Load




Derating Output Current Versus Ambient Temperature and Airflow  
 $V_{in}=V_{in\ nom}$

## Characteristic Curves


All test conditions are at 25°C. The figures are identical for MAU305




Efficiency Versus Output Current




Efficiency Versus Input Voltage  
Full Load




Output Voltage Versus Output Current



Typical Output Ripple and Noise  
 $V_{in}=V_{in\ nom}$ ; Full Load




Typical Input Start-Up and Output Rise Characteristic  
 $V_{in}=V_{in\ nom}$ ; Full Load




Derating Output Current Versus Ambient Temperature and Airflow  
 $V_{in}=V_{in\ nom}$

## Characteristic Curves


All test conditions are at 25°C. The figures are identical for MAU306




Efficiency Versus Output Current



Efficiency Versus Input Voltage  
Full Load




Output Voltage Versus Output Current




Typical Output Ripple and Noise

$V_{in}=V_{in\ nom}$ ; Full Load



Typical Input Start-Up and Output Rise Characteristic

$V_{in}=V_{in\ nom}$ ; Full Load




Derating Output Current Versus Ambient Temperature and Airflow


$V_{in}=V_{in\ nom}$

## Characteristic Curves


All test conditions are at 25°C. The figures are identical for MAU307




Efficiency Versus Output Current




Efficiency Versus Input Voltage  
Full Load




Output Voltage Versus Output Current



Typical Output Ripple and Noise  
 $V_{in}=V_{in\ nom}$ ; Full Load




Typical Input Start-Up and Output Rise Characteristic  
 $V_{in}=V_{in\ nom}$ ; Full Load




Derating Output Current Versus Ambient Temperature and Airflow  
 $V_{in}=V_{in\ nom}$

## Characteristic Curves


All test conditions are at 25°C. The figures are identical for MAU311




Efficiency Versus Output Current




Efficiency Versus Input Voltage  
Full Load




Output Voltage Versus Output Current



Typical Output Ripple and Noise  
 $V_{in}=V_{in\ nom}$ ; Full Load




Typical Input Start-Up and Output Rise Characteristic  
 $V_{in}=V_{in\ nom}$ ; Full Load




Derating Output Current Versus Ambient Temperature and Airflow  
 $V_{in}=V_{in\ nom}$

## Characteristic Curves


All test conditions are at 25°C. The figures are identical for MAU312




Efficiency Versus Output Current




Efficiency Versus Input Voltage  
Full Load




Output Voltage Versus Output Current



Typical Output Ripple and Noise  
 $V_{in}=V_{in\ nom}$ ; Full Load




Typical Input Start-Up and Output Rise Characteristic  
 $V_{in}=V_{in\ nom}$ ; Full Load




Derating Output Current Versus Ambient Temperature and Airflow  
 $V_{in}=V_{in\ nom}$

## Characteristic Curves


All test conditions are at 25°C. The figures are identical for MAU313




Efficiency Versus Output Current




Efficiency Versus Input Voltage  
Full Load




Output Voltage Versus Output Current



Typical Output Ripple and Noise  
 $V_{in}=V_{in\ nom}$ ; Full Load




Typical Input Start-Up and Output Rise Characteristic  
 $V_{in}=V_{in\ nom}$ ; Full Load




Derating Output Current Versus Ambient Temperature and Airflow  
 $V_{in}=V_{in\ nom}$

## Characteristic Curves


All test conditions are at 25°C. The figures are identical for MAU314




Efficiency Versus Output Current




Efficiency Versus Input Voltage  
Full Load




Output Voltage Versus Output Current



Typical Output Ripple and Noise  
 $V_{in}=V_{in\ nom}$ ; Full Load




Typical Input Start-Up and Output Rise Characteristic  
 $V_{in}=V_{in\ nom}$ ; Full Load




Derating Output Current Versus Ambient Temperature and Airflow  
 $V_{in}=V_{in\ nom}$

## Characteristic Curves


All test conditions are at 25°C. The figures are identical for MAU315




Efficiency Versus Output Current




Efficiency Versus Input Voltage  
Full Load




Output Voltage Versus Output Current



Typical Output Ripple and Noise  
 $V_{in}=V_{in\ nom}$ ; Full Load




Typical Input Start-Up and Output Rise Characteristic  
 $V_{in}=V_{in\ nom}$ ; Full Load




Derating Output Current Versus Ambient Temperature and Airflow  
 $V_{in}=V_{in\ nom}$

## Characteristic Curves


All test conditions are at 25°C. The figures are identical for MAU316




Efficiency Versus Output Current




Efficiency Versus Input Voltage  
Full Load




Output Voltage Versus Output Current



Typical Output Ripple and Noise  
 $V_{in}=V_{in\ nom}$ ; Full Load




Typical Input Start-Up and Output Rise Characteristic  
 $V_{in}=V_{in\ nom}$ ; Full Load




Derating Output Current Versus Ambient Temperature and Airflow  
 $V_{in}=V_{in\ nom}$

## Characteristic Curves


All test conditions are at 25°C. The figures are identical for MAU317




Efficiency Versus Output Current



Efficiency Versus Input Voltage  
Full Load




Output Voltage Versus Output Current



Typical Output Ripple and Noise  
 $V_{in}=V_{in\ nom}$ ; Full Load




Typical Input Start-Up and Output Rise Characteristic  
 $V_{in}=V_{in\ nom}$ ; Full Load




Derating Output Current Versus Ambient Temperature and Airflow  
 $V_{in}=V_{in\ nom}$

## Characteristic Curves


All test conditions are at 25°C. The figures are identical for MAU321




Efficiency Versus Output Current




Efficiency Versus Input Voltage  
Full Load




Output Voltage Versus Output Current



Typical Output Ripple and Noise  
 $V_{in}=V_{in\ nom}$ ; Full Load




Typical Input Start-Up and Output Rise Characteristic  
 $V_{in}=V_{in\ nom}$ ; Full Load




Derating Output Current Versus Ambient Temperature and Airflow  
 $V_{in}=V_{in\ nom}$

## Characteristic Curves


All test conditions are at 25°C. The figures are identical for MAU322




Efficiency Versus Output Current



Efficiency Versus Input Voltage  
Full Load




Output Voltage Versus Output Current



Typical Output Ripple and Noise  
 $V_{in}=V_{in\ nom}$ ; Full Load




Typical Input Start-Up and Output Rise Characteristic  
 $V_{in}=V_{in\ nom}$ ; Full Load




Derating Output Current Versus Ambient Temperature and Airflow  
 $V_{in}=V_{in\ nom}$

## Characteristic Curves


All test conditions are at 25°C. The figures are identical for MAU323




Efficiency Versus Output Current




Efficiency Versus Input Voltage  
Full Load




Output Voltage Versus Output Current



Typical Output Ripple and Noise  
 $V_{in}=V_{in\ nom}$ ; Full Load




Typical Input Start-Up and Output Rise Characteristic  
 $V_{in}=V_{in\ nom}$ ; Full Load




Derating Output Current Versus Ambient Temperature and Airflow  
 $V_{in}=V_{in\ nom}$

## Characteristic Curves


All test conditions are at 25°C. The figures are identical for MAU324




Efficiency Versus Output Current



Efficiency Versus Input Voltage  
Full Load




Output Voltage Versus Output Current



Typical Output Ripple and Noise  
 $V_{in}=V_{in\ nom}$ ; Full Load




Typical Input Start-Up and Output Rise Characteristic  
 $V_{in}=V_{in\ nom}$ ; Full Load




Derating Output Current Versus Ambient Temperature and Airflow  
 $V_{in}=V_{in\ nom}$

## Characteristic Curves


All test conditions are at 25°C. The figures are identical for MAU325




Efficiency Versus Output Current




Efficiency Versus Input Voltage  
Full Load




Output Voltage Versus Output Current



Typical Output Ripple and Noise  
 $V_{in}=V_{in\ nom}$ ; Full Load




Typical Input Start-Up and Output Rise Characteristic  
 $V_{in}=V_{in\ nom}$ ; Full Load




Derating Output Current Versus Ambient Temperature and Airflow  
 $V_{in}=V_{in\ nom}$

## Characteristic Curves


All test conditions are at 25°C. The figures are identical for MAU326




Efficiency Versus Output Current



Efficiency Versus Input Voltage  
Full Load




Output Voltage Versus Output Current




Typical Output Ripple and Noise

$V_{in}=V_{in\ nom}$ ; Full Load



Typical Input Start-Up and Output Rise Characteristic

$V_{in}=V_{in\ nom}$ ; Full Load




Derating Output Current Versus Ambient Temperature and Airflow


$V_{in}=V_{in\ nom}$

## Characteristic Curves


All test conditions are at 25°C. The figures are identical for MAU327




Efficiency Versus Output Current




Efficiency Versus Input Voltage  
Full Load




Output Voltage Versus Output Current



Typical Output Ripple and Noise  
 $V_{in}=V_{in\ nom}$ ; Full Load





Typical Input Start-Up and Output Rise Characteristic  
 $V_{in}=V_{in\ nom}$ ; Full Load



Derating Output Current Versus Ambient Temperature and Airflow  
 $V_{in}=V_{in\ nom}$

### Package Specifications

Mechanical Dimensions	
	19.5 [0.77] 0.5 [0.02] 0.5 [0.02] 3.2 [0.13] 10.2 [0.40]
	18.5 [0.73] 2.1 [0.08] 2.54 [0.100] 5.08 [0.200] 2x2.54 [2x0.100] 0.50 [0.020] 0.25 [0.010] 1.3 [0.05] 7.6 [0.30]


Pin Connections		
Pin	Single Output	Dual Output
1	+Vin	+Vin
2	-Vin	-Vin
4	-Vout	-Vout
5	No Pin	Common
6	+Vout	+Vout

- All dimensions in mm (inches)
- Tolerance: X.X±0.25 (X.XX±0.01)  
X.XX±0.13 (X.XXX±0.005)
- Pins ±0.05(±0.002)

### Physical Characteristics

Case Size	:	19.5x7.6x10.2mm (0.77x0.30x0.40 inches)
Case Material	:	Non-Conductive Black Plastic (flammability to UL 94V-0 rated)
Pin Material	:	Alloy 42
Weight	:	2.7g


### Recommended Pad Layout for Single & Dual Output Converter



## Test Setup

### Peak-to-Peak Output Noise Measurement Test

Use a  $C_{out}$   $0.33\mu F$  ceramic capacitor. Scope measurement should be made by using a BNC socket, measurement bandwidth is 0-20 MHz. Position the load between 50 mm and 75 mm from the DC-DC Converter.




## Technical Notes

### Maximum Capacitive Load

The MAU300 series has limitation of maximum connected capacitance at the output. The power module may be operated in current limiting mode during start-up, affecting the ramp-up and the startup time. For optimum performance we recommend  $390\mu F$  maximum capacitive load for dual outputs and  $470\mu F$  capacitive load for single outputs. The maximum capacitance can be found in the data sheet.


### Input Source Impedance

The power module should be connected to a low ac-impedance input source. Highly inductive source impedances can affect the stability of the power module. In applications where power is supplied over long lines and output loading is high, it may be necessary to use a capacitor at the input to ensure startup. Capacitor mounted close to the power module helps ensure stability of the unit, it is recommended to use a good quality low Equivalent Series Resistance (ESR < 1.0Ω at 100 kHz) capacitor of a  $2.2\mu F$  for the 5V input devices, a  $1.0\mu F$  for the 12V input devices and a  $0.47\mu F$  for the 24V devices.




### Output Ripple Reduction


A good quality low ESR capacitor placed as close as practicable across the load will give the best ripple and noise performance. To reduce output ripple, it is recommended to use  $1.5\mu F$  capacitors at the output.



### Thermal Considerations

Many conditions affect the thermal performance of the power module, such as orientation, airflow over the module and board spacing. To avoid exceeding the maximum temperature rating of the components inside the power module, the case temperature must be kept below 105°C. The derating curves are determined from measurements obtained in a test setup.




**Packaging Information**

Unit: mm  
10 PCS per TUBE

**Wave Soldering Considerations**

Lead free wave solder profile



Zone	Reference Parameter
Preheat	Rise temp. speed : 3°C/sec max.
zone	Preheat temp. : 100~130°C
Actual	Peak temp. : 250~260°C
heating	Peak time(T1+T2) : 4~6 sec

**Hand Welding Parameter**

Reference Solder: Sn-Ag-Cu : Sn-Cu : Sn-Ag

Hand Welding: Soldering iron : Power 60W

Welding Time: 2~4 sec

Temp.: 380~400°C

**Part Number Structure**

M	A	U	30	1
	<b>Package Type</b> SIP-7	<b>Output Regulation</b> Unregulated	<b>Input Voltage Range</b> 30: 4.5 ~ 5.5 VDC 31: 10.8 ~ 13.2 VDC 32: 21.6 ~ 26.4 VDC	<b>Output Voltage</b> 1: 3.3 VDC 2: 5 VDC 3: 12 VDC 4: 15 VDC 5: ±5 VDC 6: ±12 VDC 7: ±15 VDC

**MTBF and Reliability**

The MTBF of MAU300 series of DC-DC converters has been calculated using

MIL-HDBK 217F NOTICE2, Operating Temperature 25°C, Ground Benign.

Model	MTBF	Unit
MAU301	3,668,042	
MAU302	3,613,370	
MAU303	3,631,412	
MAU304	3,631,412	
MAU305	3,305,785	
MAU306	3,848,004	
MAU307	3,807,710	
MAU311	3,786,086	
MAU312	3,727,866	
MAU313	3,747,073	
MAU314	3,747,073	
MAU315	3,401,361	
MAU316	3,558,719	
MAU317	3,524,229	
MAU321	3,836,930	
MAU322	3,777,148	
MAU323	3,796,867	
MAU324	3,796,867	
MAU325	3,442,341	
MAU326	3,605,227	
MAU327	3,569,835	

Hours