



MINMAX[®]

MAU400 Series

Electric Characteristic Note

MAU400 Series EC Note

DC-DC CONVERTER 1W, Reinforced Insulation, Medical Safety

Features

- ▶ Industrial Standard SIP-7 Package
- ▶ Unregulated Output Voltage
- ▶ I/O Isolation 3000VAC with Reinforced Insulation, rated for 300Vrms Working Voltage
- ▶ Operating Ambient Temp. Range -25°C to +85°C
- ▶ Medical EMC Standard with 4th Edition of EMI EN 55011 and EMS EN 60601-1-2 Approved
- ▶ Medical Safety with 1xMOPP & 2xMOOP per 3.2 Edition of IEC/EN 60601-1 & ANSI/AAMI ES60601-1 Approved
- ▶ Risk Management Report Acquisition according to ISO 14971
- ▶ UL/cUL/IEC/EN 62368-1(60950-1) Safety Approval & CE Marking



Applications

- ▶ Distributed power architectures
- ▶ Workstations
- ▶ Computer equipment
- ▶ Communications equipment

Product Overview

Introducing the MINMAX MAU400 series - 1W isolated DC-DC converter modules designed to meet stringent safety and performance standards. These modules offer a remarkable high I/O isolation voltage of 3000VAC with reinforced insulation, rated for a dependable 300Vrms working voltage within a compact SIP package.

With a diverse range of 12 models catering to 5VDC or 12VDC input voltages and featuring options for single or dual output voltages, the MAU400 series caters to a variety of application needs. This product stands out as the optimal solution for applications in industrial controls and instrumentation, consumer electronics, and scenarios where a certified supplementary or reinforced insulation system is essential to comply with rigorous safety standards.

The MAU400 series is approved to IEC/EN/ES 60601-1 3.2 Edition for 1xMOPP & 2xMOOP and comes with an ISO 14971 Medical Device risk management file, ensuring not only adherence to high-performance standards but also compliance with strict safety benchmarks.

Table of contents

Model Selection Guide	P2	Package Specifications	P17
Input Specifications.....	P2	Recommended Pad Layout for Single & Dual Output Converter.....	P17
Output Specifications.....	P2	Test Setup.....	P18
Output Voltage Tolerance	P3	Technical Notes	P18
Isolation, Safety Standards.....	P3	Packaging Information for Tube	P19
General Specifications.....	P3	Wave Soldering Considerations	P19
EMC Specifications.....	P4	Hand Welding Parameter	P19
Environmental Specifications	P4	Part Number Structure	P20
Characteristic Curves	P5	MTBF and Reliability	P20


Model Selection Guide								
Model Number	Input Voltage (Range)	Output Voltage	Output Current	Input Current		Load Regulation	Max. capacitive Load	Efficiency (typ.)
				Max.	@Max. Load			@No Load
	VDC	VDC	mA	mA(typ.)	mA(typ.)	% (max.)	μF	%
MAU401	5 (4.5 ~ 5.5)	5	200	303	55	10	680	66
MAU402		12	80	291		8		66
MAU403		15	65	295		8		66
MAU404		±5	±100	303		10	220#	66
MAU405		±12	±40	267		8		72
MAU406		±15	±35	287		8		73
MAU411	12 (10.8 ~ 13.2)	5	200	126	30	10	680	66
MAU412		12	80	121		8		66
MAU413		15	65	123		8		66
MAU414		±5	±100	126		10	220#	66
MAU415		±12	±40	108		8		74
MAU416		±15	±35	117		8		75

For each output


Input Specifications					
Parameter	Model	Min.	Typ.	Max.	Unit
Input Voltage Range	5V Input Models	4.5	5	5.5	VDC
	12V Input Models	10.8	12	13.2	
Input Surge Voltage (1 sec. max.)	5V Input Models	-0.7	---	9	
	12V Input Models	-0.7	---	29	
Input Filter	All Models	Internal LC Type			

Output Specifications					
Parameter	Conditions	Min.	Typ.	Max.	Unit
Output Voltage Setting Accuracy		---	±1.0	±3.0	%Vnom.
Output Voltage Balance	Dual Output, Balanced Loads	---	±0.1	±1.0	%
Line Regulation	For Vin Change of 1%	---	±1.2	±1.5	%
Load Regulation	Io=20% to 100%	See Model Selection Guide (Operation at lower load will not damage the converter, but it may not meet all specifications)			
Ripple & Noise	0-20MHz Bandwidth	---	---	150	mV _{P-P}
Temperature Coefficient		---	±0.01	±0.02	%/°C
Short Circuit Protection	0.5 Second Max., Automatic Recovery				


Output Voltage Tolerance



Output Voltage VS Output Load Current
For 5V & ±5V Output Models



Output Voltage VS Output Load Current
For 12V, 15V, ±12V, ±15V Output Models



Output Voltage VS Input Voltage Range

Isolation, Safety Standards

Parameter	Conditions	Min.	Typ.	Max.	Unit
I/O Isolation Voltage	60 Seconds Reinforced insulation, rated for 300Vrms working voltage	3000	---	---	VAC
I/O Isolation Resistance	500 VDC	10	---	---	GΩ
I/O Isolation Capacitance	100kHz, 1V	---	15	20	pF
Safety Standards	UL/cUL 60950-1, CSA C22.2 No. 60950-1				
	ANSI/AAMI ES 60601-1, CAN/CSA-C22.2 No. 60601-1				
	IEC/EN 60950-1, IEC/EN 60601-1 3.2 Edition 1xMOPP & 2xMOOP				
Safety Approvals	UL/cUL 60950-1 recognition (UL certificate), IEC/EN 60950-1 (CB-report)				
	UL/cUL 62368-1 recognition (UL certificate), IEC/EN 62368-1 (CB-report)				
	ANSI/AAMI ES 60601-1 1xMOPP & 2xMOOP recognition (UL certificate), IEC/EN 60601-1 3.2 Edition (CB-report)				

General Specifications

Parameter	Conditions	Min.	Typ.	Max.	Unit
Switching Frequency		50	80	100	kHz
MTBF (calculated)	MIL-HDBK-217F@25°C, Ground Benign	2,000,000	---	---	Hours




EMC Specifications				
Parameter	Standards & Level			Performance
EMI	Conduction	EN 55011, EN 55032, EN 61000-6-3		Without external components Class A
	Radiation	EN 61000-6-4		
EMS	EN 60601-1-2 4 th , EN 55035, EN 61000-6-1, EN 61000-6-2			
	ESD	Direct discharge		Indirect discharge HCP & VCP Contact ± 8kV
		EN 61000-4-2 Air ± 15kV		
	Radiated immunity	EN 61000-4-3 10V/m		A
	Fast transient	EN 61000-4-4 ±2kV		A
	Surge	EN 61000-4-5 ±1kV		A
	Conducted immunity	EN 61000-4-6 10Vrms		A
	PFMF	EN 61000-4-8 100A/m.1000A/m(1 sec)		A

Environmental Specifications				
Parameter	Min.	Max.	Unit	
Operating Ambient Temperature Range (See Power Derating Curve)	-25	+85	°C	
Case Temperature	---	+105	°C	
Storage Temperature Range	-50	+125	°C	
Humidity (non condensing)	---	95	% rel. H	
Lead Temperature (1.5mm from case for 10Sec.)	---	260	°C	


Notes	
1	Specifications typical at Ta=+25°C, resistive load, nominal input voltage and rated output current unless otherwise noted.
2	These power converters require a minimum output loading to maintain specified regulation, operation under no-load conditions will not damage these modules; however they may not meet all specifications listed.
3	We recommend to protect the converter by a slow blow fuse in the input supply line.
4	Other input and output voltage may be available, please contact MINMAX.
5	Specifications are subject to change without notice.
6	The repeated high voltage isolation testing of the converter can degrade isolation capability, to a lesser or greater degree depending on materials, construction, environment and reflow solder process. Any material is susceptible to eventual chemical degradation when subject to very high applied voltages thus implying that the number of tests should be strictly limited. We therefore strongly advise against repeated high voltage isolation testing, but if it is absolutely required, that the voltage be reduced by 20% from specified test voltage. Furthermore, the high voltage isolation capability after reflow solder process should be evaluated as it is applied on system.

Characteristic Curves


All test conditions are at 25°C The figures are identical for MAU401



Typical Output Ripple and Noise
 $V_{in}=V_{in nom}$; Full Load






Typical Input Start-Up and Output Rise Characteristic
 $V_{in}=V_{in nom}$; Full Load




Derating Output Current Versus Ambient Temperature and Airflow
 $V_{in}=V_{in nom}$

Characteristic Curves


All test conditions are at 25°C The figures are identical for MAU402



Typical Output Ripple and Noise
 $V_{in}=V_{in nom}$; Full Load






Typical Input Start-Up and Output Rise Characteristic
 $V_{in}=V_{in nom}$; Full Load




Derating Output Current Versus Ambient Temperature and Airflow
 $V_{in}=V_{in nom}$

Characteristic Curves


All test conditions are at 25°C The figures are identical for MAU403



Typical Output Ripple and Noise
 $V_{in}=V_{in\ nom}$; Full Load






Typical Input Start-Up and Output Rise Characteristic
 $V_{in}=V_{in\ nom}$; Full Load




Derating Output Current Versus Ambient Temperature and Airflow
 $V_{in}=V_{in\ nom}$

Characteristic Curves


All test conditions are at 25°C The figures are identical for MAU404



Typical Output Ripple and Noise
 $V_{in} = V_{in\ nom}$; Full Load






Typical Input Start-Up and Output Rise Characteristic
 $V_{in} = V_{in\ nom}$; Full Load




Derating Output Current Versus Ambient Temperature and Airflow
 $V_{in} = V_{in\ nom}$

Characteristic Curves


All test conditions are at 25°C The figures are identical for MAU405



Typical Output Ripple and Noise
 $V_{in}=V_{in\ nom}$; Full Load






Typical Input Start-Up and Output Rise Characteristic
 $V_{in}=V_{in\ nom}$; Full Load




Derating Output Current Versus Ambient Temperature and Airflow
 $V_{in}=V_{in\ nom}$

Characteristic Curves


All test conditions are at 25°C The figures are identical for MAU406



Typical Output Ripple and Noise
 $V_{in}=V_{in\ nom}$; Full Load






Typical Input Start-Up and Output Rise Characteristic
 $V_{in}=V_{in\ nom}$; Full Load




Derating Output Current Versus Ambient Temperature and Airflow
 $V_{in}=V_{in\ nom}$

Characteristic Curves


All test conditions are at 25°C The figures are identical for MAU411



Typical Output Ripple and Noise
 $V_{in} = V_{in\ nom}$; Full Load






Typical Input Start-Up and Output Rise Characteristic
 $V_{in} = V_{in\ nom}$; Full Load




Derating Output Current Versus Ambient Temperature and Airflow
 $V_{in} = V_{in\ nom}$

Characteristic Curves


All test conditions are at 25°C The figures are identical for MAU412



Typical Output Ripple and Noise
 $V_{in}=V_{in\ nom}$; Full Load






Typical Input Start-Up and Output Rise Characteristic
 $V_{in}=V_{in\ nom}$; Full Load




Derating Output Current Versus Ambient Temperature and Airflow
 $V_{in}=V_{in\ nom}$

Characteristic Curves


All test conditions are at 25°C The figures are identical for MAU413



Typical Output Ripple and Noise
 $V_{in}=V_{in nom}$; Full Load






Typical Input Start-Up and Output Rise Characteristic
 $V_{in}=V_{in nom}$; Full Load




Derating Output Current Versus Ambient Temperature and Airflow
 $V_{in}=V_{in nom}$

Characteristic Curves


All test conditions are at 25°C The figures are identical for MAU414



Typical Output Ripple and Noise
 $V_{in}=V_{in\ nom}$; Full Load






Typical Input Start-Up and Output Rise Characteristic
 $V_{in}=V_{in\ nom}$; Full Load




Derating Output Current Versus Ambient Temperature and Airflow
 $V_{in}=V_{in\ nom}$

Characteristic Curves


All test conditions are at 25°C The figures are identical for MAU415



Typical Output Ripple and Noise
 $V_{in}=V_{in\ nom}$; Full Load






Typical Input Start-Up and Output Rise Characteristic
 $V_{in}=V_{in\ nom}$; Full Load




Derating Output Current Versus Ambient Temperature and Airflow
 $V_{in}=V_{in\ nom}$

Characteristic Curves


All test conditions are at 25°C The figures are identical for MAU416



Typical Output Ripple and Noise
 $V_{in}=V_{in nom}$; Full Load




Typical Input Start-Up and Output Rise Characteristic
 $V_{in}=V_{in nom}$; Full Load



Derating Output Current Versus Ambient Temperature and Airflow
 $V_{in}=V_{in nom}$

Package Specifications



Pin Connections


Pin	Single Output	Dual Output
1	+Vin	+Vin
2	-Vin	-Vin
5	-Vout	-Vout
6	No Pin	Common
7	+Vout	+Vout

- ▶ All dimensions in mm (inches)
- ▶ Tolerance: X.X±0.5 (X.XX±0.02)
X.XX±0.13 (X.XXX±0.005)
- ▶ Pins ±0.05 (±0.002)

Physical Characteristics

Case Size	: 22.0x7.5x12.5mm (0.87x0.30x0.49 inches)
Case Material	: Plastic resin (flammability to UL 94V-0 rated)
Pin Material	: Alloy 42
Weight	: 3.9g


Recommended Pad Layout for Single & Dual Output Converter



Test Setup

Peak-to-Peak Output Noise Measurement Test

Use a Cout 0.33 μ F ceramic capacitor. Scope measurement should be made by using a BNC socket, measurement bandwidth is 0-20 MHz. Position the load between 50 mm and 75 mm from the DC-DC Converter.




Technical Notes

Maximum Capacitive Load

The MAU400 series has limitation of maximum connected capacitance at the output. The power module may be operated in current limiting mode during start-up, affecting the ramp-up and the startup time. For optimum performance we recommend 220 μ F maximum capacitive load for dual outputs and 680 μ F capacitive load for single outputs. The maximum capacitance can be found in the data sheet.


Input Source Impedance

The power module should be connected to a low ac-impedance input source. Highly inductive source impedances can affect the stability of the power module. In applications where power is supplied over long lines and output loading is high, it may be necessary to use a capacitor at the input to ensure startup. Capacitor mounted close to the power module helps ensure stability of the unit, it is recommended to use a good quality low Equivalent Series Resistance (ESR < 1.0 Ω at 100 kHz) capacitor of a 2.2 μ F for the 5V input devices, a 1.0 μ F for the 12V input devices.




Output Ripple Reduction

A good quality low ESR capacitor placed as close as practicable across the load will give the best ripple and noise performance. To reduce output ripple, it is recommended to use 1.5 μ F capacitors at the output.




Thermal Considerations

Many conditions affect the thermal performance of the power module, such as orientation, airflow over the module and board spacing. To avoid exceeding the maximum temperature rating of the components inside the power module, the case temperature must be kept below 105°C. The derating curves are determined from measurements obtained in a test setup.




Packaging Information for Tube



Unit: mm
10 PCS per TUBE

Wave Soldering Considerations

Lead free wave solder profile



Zone	Reference Parameter
Preheat	Rise temp. speed : 3°C/sec max.
zone	Preheat temp. : 100~130°C
Actual	Peak temp. : 250~260°C
heating	Peak time(T1+T2) : 4~6 sec

Hand Welding Parameter

Reference Solder: Sn-Ag-Cu : Sn-Cu : Sn-Ag

Hand Welding: Soldering iron : Power 60W

Welding Time: 2~4 sec

Temp.: 380~400°C

Part Number Structure

M	A	U	40	1																								
	<table border="1"> <tr> <td>Package Type</td> <td>SIP-7</td> </tr> </table>	Package Type	SIP-7	<table border="1"> <tr> <td>Output Regulation</td> <td>Unregulated</td> </tr> </table>	Output Regulation	Unregulated	<table border="1"> <tr> <td colspan="2">Input Voltage Range</td> </tr> <tr> <td>40:</td> <td>4.5 ~ 5.5 VDC</td> </tr> <tr> <td>41:</td> <td>10.8 ~ 13.2 VDC</td> </tr> </table>	Input Voltage Range		40:	4.5 ~ 5.5 VDC	41:	10.8 ~ 13.2 VDC	<table border="1"> <tr> <td colspan="2">Output Voltage</td> </tr> <tr> <td>1:</td> <td>5 VDC</td> </tr> <tr> <td>2:</td> <td>12 VDC</td> </tr> <tr> <td>3:</td> <td>15 VDC</td> </tr> <tr> <td>4:</td> <td>±5 VDC</td> </tr> <tr> <td>5:</td> <td>±12 VDC</td> </tr> <tr> <td>6:</td> <td>±15 VDC</td> </tr> </table>	Output Voltage		1:	5 VDC	2:	12 VDC	3:	15 VDC	4:	±5 VDC	5:	±12 VDC	6:	±15 VDC
Package Type	SIP-7																											
Output Regulation	Unregulated																											
Input Voltage Range																												
40:	4.5 ~ 5.5 VDC																											
41:	10.8 ~ 13.2 VDC																											
Output Voltage																												
1:	5 VDC																											
2:	12 VDC																											
3:	15 VDC																											
4:	±5 VDC																											
5:	±12 VDC																											
6:	±15 VDC																											

MTBF and Reliability

The MTBF of MAU400 series of DC-DC converters has been calculated using

MIL-HDBK 217F NOTICE2, Operating Temperature 25°C, Ground Benign.

Model	MTBF	Unit
MAU401	2,900,953	Hours
MAU402	2,926,421	
MAU403	2,875,924	
MAU404	2,188,868	
MAU405	2,398,082	
MAU406	2,364,865	
MAU411	2,911,814	
MAU412	2,937,474	
MAU413	2,886,598	
MAU414	2,138,058	
MAU415	2,364,865	
MAU416	2,364,865	