



MINMAX[®]

MIW03M Series


Electric Characteristic Note

MIW03M Series EC Note

DC-DC CONVERTER 3.5W, DIP Package

Features

- ▶ Industrial Standard DIP-24 Package
- ▶ Wide 2:1 Input Voltage Range
- ▶ Fully Regulated Output Voltage
- ▶ I/O Isolation 5000VAC with Reinforced Insulation, rated for 250Vrms Working Voltage
- ▶ Creepage & Clearance Distance meet 8mm
- ▶ Low I/O Leakage Current < 2μA
- ▶ Operating Ambient Temp. Range -40°C to 96°C
- ▶ No Min. Load Requirement
- ▶ Under-Voltage, Overload/Voltage and Short Circuit Protection
- ▶ Conducted EMI EN 55011 Class A Approved
- ▶ Medical EMC Standard with 4th Edition of EMI EN 55011 and EMS EN 60601-1-2 Approved
- ▶ Medical Safety with 2xMOPP per 3.2 Edition of IEC/EN 60601-1 & ANSI/AAMI ES60601-1 Approved with CE Marking
- ▶ Risk Management Report Acquisition according to ISO 14971



Applications

- ▶ Distributed power architectures
- ▶ Workstations
- ▶ Computer equipment
- ▶ Communications equipment

Product Overview

Introducing the MINMAX MIW03M series - an innovative range of high-performance 3.5W medical-approved DC-DC converters encapsulated in a DIP-24 package, purposefully designed for medical applications. With an extensive selection of 21 models supporting input voltages of 5, 12, 24, and 48VDC, featuring a wide 2:1 input range and fixed output voltage, this series ensures adaptability to diverse medical device specifications.

The MIW03M series boasts an I/O isolation specified for 5000VAC with reinforced insulation, rated for a reliable 250Vrms working voltage. Advanced features include under-voltage, overload, over-voltage, and short-circuit protection, along with no minimum load requirement, conducted EMI EN 55011 class A approval, low I/O leakage current of 2μA max, and an operating ambient temperature range from -40°C to +96°C without derating, achieved through high efficiency up to 87%.

Aligned with the 4th edition medical EMC standard, the MIW03M series holds medical safety approval with 2xMOPP (Means Of Patient Protection) per the 3.2 Edition of IEC/EN 60601-1 & ANSI/AAMI ES 60601-1, incorporating an 8mm creepage and clearance.

In adherence to ISO 14971 Medical Device Risk Management, the MIW03M series undergoes a thorough risk assessment process. This ensures not only compliance with high-performance standards but also alignment with the stringent safety benchmarks outlined in ISO 14971. Elevate your medical devices with the MINMAX MIW03M series - the integration of advanced technology, safety, performance, and Medical Device Risk Management Report Acquisition.

Table of contents

Model Selection Guide	P2	Recommended Pad Layout for Single & Dual Output Converter.....	P26
Input Specifications.....	P2	Test Setup.....	P27
Output Specifications.....	P3	Technical Notes	P27
Isolation, Safety Standards.....	P3	Packaging Information for Tube	P28
General Specifications.....	P3	Wave Soldering Considerations	P28
EMC Specifications.....	P3	Hand Welding Parameter	P28
Environmental Specifications	P4	Part Number Structure	P29
Characteristic Curves	P5	MTBF and Reliability	P29
Package Specifications	P26		

Model Selection Guide								
Model Number	Input Voltage (Range)	Output Voltage	Output Current	Input Current		Over Voltage Protection	Max. capacitive Load	Efficiency (typ.)
			Max.	@Max. Load	@No Load			@Max. Load
	VDC	VDC	mA	mA(typ.)	mA(typ.)	VDC	μF	%
MIW03-05S05M	5 (4.5 ~ 9)	5	700	843	20	6.2	750	83
MIW03-05S058M		5.8	600	839		6.2	560	83
MIW03-05S12M		12	290	829		15	130	84
MIW03-05S15M		15	235	839	35	18	100	84
MIW03-05D12M		±12	±145	829		±15	75#	84
MIW03-05D15M		±15	±115	821		±18	56#	84
MIW03-12S05M	12 (9 ~ 18)	5	700	351	8	6.2	750	83
MIW03-12S12M		12	290	333		15	130	87
MIW03-12S15M		15	235	338		18	100	87
MIW03-12D12M		±12	±145	333	13	±15	75#	87
MIW03-12D15M		±15	±115	330		±18	56#	87
MIW03-24S05M		5	700	176		6	6.2	750
MIW03-24S12M	12	290	169	15	130		86	
MIW03-24S15M	15	235	169	18	100		87	
MIW03-24D12M	±12	±145	167	±15	75#		87	
MIW03-24D15M	±15	±115	167	±18	56#		86	
MIW03-48S05M	48 (36 ~ 75)	5	700	88	4		6.2	750
MIW03-48S12M		12	290	84		15	130	86
MIW03-48S15M		15	235	86		18	100	85
MIW03-48D12M		±12	±145	86	±15	75#	84	
MIW03-48D15M		±15	±115	86	±18	56#	84	

For each output

Input Specifications						
Parameter	Conditions / Model	Min.	Typ.	Max.	Unit	
Input Surge Voltage (1 sec. max.)	5V Input Models	-0.7	---	15	VDC	
	12V Input Models	-0.7	---	25		
	24V Input Models	-0.7	---	50		
	48V Input Models	-0.7	---	100		
Start-Up Threshold Voltage	5V Input Models	---	---	4.5		
	12V Input Models	---	---	9		
	24V Input Models	---	---	18		
	48V Input Models	---	---	36		
Under Voltage Shutdown	5V Input Models	---	4	---		
	12V Input Models	---	8	---		
	24V Input Models	---	16	---		
	48V Input Models	---	34	---		
Start Up Time (Power On)	Nominal Vin and Constant Resistive Load	---	---	30	ms	
Input Filter	All Models	Internal Pi Type				

Output Specifications						
Parameter	Conditions		Min.	Typ.	Max.	Unit
Output Voltage Setting Accuracy			---	---	±1.0	%Vnom.
Output Voltage Balance	Dual Output, Balanced Loads		---	±0.5	±2.0	%
Line Regulation	Vin=Min. to Max. @Full Load		---	---	±0.5	%
Load Regulation	Io=0% to 100%		---	---	±0.5	%
Load Cross Regulation (Dual Output)	Asymmetrical Load 25%/100% Full Load		---	---	±5.0	%
Minimum Load	No minimum Load Requirement					
Ripple & Noise	0-20 MHz Bandwidth	Measured with a 1µF MLCC	---	---	70	mV _{P-P}
Transient Recovery Time	25% Load Step Change		---	300	---	µs
Transient Response Deviation			---	±3	±5	%
Temperature Coefficient			---	±0.01	±0.02	%/°C
Over Load Protection			---	150	---	%
Short Circuit Protection	Continuous, Automatic Recovery (Hiccup Mode 0.5Hz typ.)					

Isolation, Safety Standards						
Parameter	Conditions		Min.	Typ.	Max.	Unit
I/O Isolation Voltage	60 Seconds Reinforced insulation, rated for 250Vrms working voltage		5000	---	---	VAC
Leakage Current	240VAC, 60Hz		---	---	2	µA
I/O Isolation Resistance	500 VDC		10	---	---	GΩ
I/O Isolation Capacitance	100kHz, 1V		---	---	40	pF
Safety Standards	ANSI/AAMI ES60601-1, CAN/CSA-C22.2 No. 60601-1 IEC/EN 60601-1 3.2 Edition 2xMOPP					
Safety Approvals	ANSI/AAMI ES60601-1 2xMOPP recognition(UL certificate), IEC/EN 60601-1 3.2 Edition(CB-report)					

General Specifications						
Parameter	Conditions		Min.	Typ.	Max.	Unit
Switching Frequency			---	330	---	kHz
MTBF(calculated)	MIL-HDBK-217F@25°C, Ground Benign		5,815,448	---	---	Hours

EMC Specifications					
Parameter	Standards & Level			Performance	
EMI ₍₅₎	Conduction	EN 55011	Without external components		Class A
	Radiation		With external components		
EMS ₍₅₎	EN 60601-1-2 4 th				
	ESD	Direct discharge	Indirect discharge HCP & VCP		A
		EN 61000-4-2 Air ± 15kV		Contact ± 8kV	
	Radiated immunity	EN 61000-4-3 10V/m			A
	Fast transient	EN 61000-4-4 ±2kV			A
	Surge	EN 61000-4-5 ±2kV			A
	Conducted immunity	EN 61000-4-6 10Vrms			A
PFMF	EN 61000-4-8 100A/m			A	

Environmental Specifications


Parameter	Min.	Max.	Unit
Operating Ambient Temperature Range (See Power Derating Curve)	-40	+96	°C
Case Temperature	---	+105	°C
Storage Temperature Range	-50	+125	°C
Humidity (non condensing)	---	95	% rel. H
Lead Temperature (1.5mm from case for 10Sec.)	---	260	°C

Notes


- 1 Specifications typical at Ta=+25°C, resistive load, nominal input voltage and rated output current unless otherwise noted.
- 2 Transient recovery time is measured to within 1% error band for a step change in output load of 75% to 100%.
- 3 We recommend to protect the converter by a slow blow fuse in the input supply line.
- 4 Other input and output voltage may be available, please contact MINMAX.
- 5 The external components might be required to meet EMI/EMS standard for some of test items. Please contact MINMAX for the solution in detail.
- 6 Specifications are subject to change without notice.
- 7 The repeated high voltage isolation testing of the converter can degrade isolation capability, to a lesser or greater degree depending on materials, construction, environment and reflow solder process. Any material is susceptible to eventual chemical degradation when subject to very high applied voltages thus implying that the number of tests should be strictly limited. We therefore strongly advise against repeated high voltage isolation testing, but if it is absolutely required, that the voltage be reduced by 20% from specified test voltage. Furthermore, the high voltage isolation capability after reflow solder process should be evaluated as it is applied on system.

Characteristic Curves


All test conditions are at 25°C The figures are identical for MIW03-05S05M




Efficiency Versus Output Current




Efficiency Versus Input Voltage Full Load




Typical Output Ripple and Noise
 $V_{in}=V_{in\ nom}$; Full Load



Transient Response to Dynamic Load Change
from 100% to 75% of Full Load ; $V_{in}=V_{in\ nom}$




Typical Input Start-Up and Output Rise Characteristic
 $V_{in}=V_{in\ nom}$; Full Load




Derating Output Current Versus Ambient Temperature and Airflow
 $V_{in}=V_{in\ nom}$

Characteristic Curves


All test conditions are at 25°C The figures are identical for MIW03-05S058M




Efficiency Versus Output Current




Efficiency Versus Input Voltage Full Load




Typical Output Ripple and Noise
 $V_{in}=V_{in\ nom}$; Full Load



Transient Response to Dynamic Load Change
from 100% to 75% of Full Load ; $V_{in}=V_{in\ nom}$




Typical Input Start-up and Output Rise Characteristic
 $V_{in}=V_{in\ nom}$; Full Load




Derating Output Current Versus Ambient Temperature and Airflow
 $V_{in}=V_{in\ nom}$

Characteristic Curves


All test conditions are at 25°C The figures are identical for MIW03-05S12M




Efficiency Versus Output Current




Efficiency Versus Input Voltage Full Load




Typical Output Ripple and Noise
 $V_{in}=V_{in\ nom}$; Full Load



Transient Response to Dynamic Load Change
from 100% to 75% of Full Load ; $V_{in}=V_{in\ nom}$




Typical Input Start-Up and Output Rise Characteristic
 $V_{in}=V_{in\ nom}$; Full Load




Derating Output Current Versus Ambient Temperature and Airflow
 $V_{in}=V_{in\ nom}$

Characteristic Curves


All test conditions are at 25°C The figures are identical for MIW03-05S15M




Efficiency Versus Output Current




Efficiency Versus Input Voltage Full Load




Typical Output Ripple and Noise
 $V_{in}=V_{in\ nom}$; Full Load



Transient Response to Dynamic Load Change
from 100% to 75% of Full Load; $V_{in}=V_{in\ nom}$




Typical Input Start-up and Output Rise Characteristic
 $V_{in}=V_{in\ nom}$; Full Load




Derating Output Current Versus Ambient Temperature and Airflow
 $V_{in}=V_{in\ nom}$

Characteristic Curves


All test conditions are at 25°C The figures are identical for MIW03-05D12M




Efficiency Versus Output Current




Efficiency Versus Input Voltage Full Load




Typical Output Ripple and Noise
 $V_{in}=V_{in\ nom}$; Full Load



Transient Response to Dynamic Load Change
from 100% to 75% of Full Load ; $V_{in}=V_{in\ nom}$




Typical Input Start-Up and Output Rise Characteristic
 $V_{in}=V_{in\ nom}$; Full Load




Derating Output Current Versus Ambient Temperature and Airflow
 $V_{in}=V_{in\ nom}$

Characteristic Curves


All test conditions are at 25°C The figures are identical for MIW03-05D15M




Efficiency Versus Output Current




Efficiency Versus Input Voltage Full Load




Typical Output Ripple and Noise
 $V_{in}=V_{in\ nom}$; Full Load



Transient Response to Dynamic Load Change
from 100% to 75% of Full Load; $V_{in}=V_{in\ nom}$









Typical Input Start-up and Output Rise Characteristic
 $V_{in}=V_{in\ nom}$; Full Load



Derating Output Current Versus Ambient Temperature and Airflow
 $V_{in}=V_{in\ nom}$


Characteristic Curves

All test conditions are at 25°C The figures are identical for MIW03-12S05M




Characteristic Curves


All test conditions are at 25°C The figures are identical for MIW03-12S12M




Efficiency Versus Output Current




Efficiency Versus Input Voltage Full Load




Typical Output Ripple and Noise
 $V_{in}=V_{in\ nom}$; Full Load



Transient Response to Dynamic Load Change
from 100% to 75% of Full Load ; $V_{in}=V_{in\ nom}$






Typical Input Start-up and Output Rise Characteristic
 $V_{in}=V_{in\ nom}$; Full Load




Derating Output Current Versus Ambient Temperature and Airflow
 $V_{in}=V_{in\ nom}$

Characteristic Curves


All test conditions are at 25°C The figures are identical for MIW03-12S15M




Typical Output Ripple and Noise
 $V_{in}=V_{in\ nom}$; Full Load



Transient Response to Dynamic Load Change
from 100% to 75% of Full Load ; $V_{in}=V_{in\ nom}$






Typical Input Start-Up and Output Rise Characteristic
 $V_{in}=V_{in\ nom}$; Full Load




Derating Output Current Versus Ambient Temperature and Airflow
 $V_{in}=V_{in\ nom}$

Characteristic Curves


All test conditions are at 25°C The figures are identical for MIW03-12D12M




Typical Output Ripple and Noise
 $V_{in}=V_{in\ nom}$; Full Load



Transient Response to Dynamic Load Change
from 100% to 75% of Full Load ; $V_{in}=V_{in\ nom}$






Typical Input Start-Up and Output Rise Characteristic
 $V_{in}=V_{in\ nom}$; Full Load




Derating Output Current Versus Ambient Temperature and Airflow
 $V_{in}=V_{in\ nom}$

Characteristic Curves


All test conditions are at 25°C The figures are identical for MIW03-12D15M




Typical Output Ripple and Noise
 $V_{in}=V_{in\ nom}$; Full Load



Transient Response to Dynamic Load Change
from 100% to 75% of Full Load ; $V_{in}=V_{in\ nom}$






Typical Input Start-Up and Output Rise Characteristic
 $V_{in}=V_{in\ nom}$; Full Load




Derating Output Current Versus Ambient Temperature and Airflow
 $V_{in}=V_{in\ nom}$

Characteristic Curves


All test conditions are at 25°C The figures are identical for MIW03-24S05M




Typical Output Ripple and Noise
 $V_{in}=V_{in\ nom}$; Full Load



Transient Response to Dynamic Load Change
from 100% to 75% of Full Load ; $V_{in}=V_{in\ nom}$




Typical Input Start-Up and Output Rise Characteristic
 $V_{in}=V_{in\ nom}$; Full Load




Derating Output Current Versus Ambient Temperature and Airflow
 $V_{in}=V_{in\ nom}$

Characteristic Curves


All test conditions are at 25°C The figures are identical for MIW03-24S12M




Efficiency Versus Output Current




Efficiency Versus Input Voltage Full Load




Typical Output Ripple and Noise
 $V_{in}=V_{in\ nom}$; Full Load



Transient Response to Dynamic Load Change
from 100% to 75% of Full Load ; $V_{in}=V_{in\ nom}$




Typical Input Start-up and Output Rise Characteristic
 $V_{in}=V_{in\ nom}$; Full Load




Derating Output Current Versus Ambient Temperature and Airflow
 $V_{in}=V_{in\ nom}$

Characteristic Curves


All test conditions are at 25°C The figures are identical for MIW03-24S15M




Efficiency Versus Output Current




Efficiency Versus Input Voltage Full Load




Typical Output Ripple and Noise
 $V_{in}=V_{in\ nom}$; Full Load



Transient Response to Dynamic Load Change
from 100% to 75% of Full Load ; $V_{in}=V_{in\ nom}$









Typical Input Start-up and Output Rise Characteristic
 $V_{in}=V_{in\ nom}$; Full Load



Derating Output Current Versus Ambient Temperature and Airflow
 $V_{in}=V_{in\ nom}$


Characteristic Curves

All test conditions are at 25°C The figures are identical for MIW03-24D12M




Characteristic Curves


All test conditions are at 25°C The figures are identical for MIW03-24D15M




Efficiency Versus Output Current




Efficiency Versus Input Voltage Full Load




Typical Output Ripple and Noise
 $V_{in}=V_{in\ nom}$; Full Load



Transient Response to Dynamic Load Change
from 100% to 75% of Full Load ; $V_{in}=V_{in\ nom}$






Typical Input Start-up and Output Rise Characteristic
 $V_{in}=V_{in\ nom}$; Full Load




Derating Output Current Versus Ambient Temperature and Airflow
 $V_{in}=V_{in\ nom}$

Characteristic Curves


All test conditions are at 25°C The figures are identical for MIW03-48S05M




Typical Output Ripple and Noise
 $V_{in}=V_{in\ nom}$; Full Load



Transient Response to Dynamic Load Change
from 100% to 75% of Full Load ; $V_{in}=V_{in\ nom}$




Typical Input Start-up and Output Rise Characteristic
 $V_{in}=V_{in\ nom}$; Full Load




Derating Output Current Versus Ambient Temperature and Airflow
 $V_{in}=V_{in\ nom}$

Characteristic Curves


All test conditions are at 25°C The figures are identical for MIW03-48S12M




Efficiency Versus Output Current




Efficiency Versus Input Voltage Full Load




Typical Output Ripple and Noise
 $V_{in}=V_{in\ nom}$; Full Load



Transient Response to Dynamic Load Change
from 100% to 75% of Full Load; $V_{in}=V_{in\ nom}$









Typical Input Start-up and Output Rise Characteristic
 $V_{in}=V_{in\ nom}$; Full Load



Derating Output Current Versus Ambient Temperature and Airflow
 $V_{in}=V_{in\ nom}$


Characteristic Curves

All test conditions are at 25°C The figures are identical for MIW03-48S15M




Characteristic Curves


All test conditions are at 25°C The figures are identical for MIW03-48D12M




Efficiency Versus Output Current




Efficiency Versus Input Voltage Full Load




Typical Output Ripple and Noise
 $V_{in}=V_{in\ nom}$; Full Load



Transient Response to Dynamic Load Change
from 100% to 75% of Full Load ; $V_{in}=V_{in\ nom}$




Typical Input Start-up and Output Rise Characteristic
 $V_{in}=V_{in\ nom}$; Full Load




Derating Output Current Versus Ambient Temperature and Airflow
 $V_{in}=V_{in\ nom}$

Characteristic Curves


All test conditions are at 25°C The figures are identical for MIW03-48D15M




Efficiency Versus Output Current




Efficiency Versus Input Voltage Full Load




Typical Output Ripple and Noise
 $V_{in}=V_{in\ nom}$; Full Load



Transient Response to Dynamic Load Change
from 100% to 75% of Full Load ; $V_{in}=V_{in\ nom}$




Typical Input Start-up and Output Rise Characteristic
 $V_{in}=V_{in\ nom}$; Full Load



Derating Output Current Versus Ambient Temperature and Airflow
 $V_{in}=V_{in\ nom}$

Package Specifications

Mechanical Dimensions



Pin Connections


Pin	Single Output	Dual Output	Diameter mm (inches)
1	+Vin	+Vin	Ø 0.6 [0.02]
11	No Pin	Common	Ø 0.6 [0.02]
12	-Vout	No Pin	Ø 0.6 [0.02]
13	+Vout	-Vout	Ø 0.6 [0.02]
15	No Pin	+Vout	Ø 0.6 [0.02]
23	-Vin	-Vin	Ø 0.6 [0.02]
24	-Vin	-Vin	Ø 0.6 [0.02]

- ▶ All dimensions in mm (inches)
- ▶ Tolerance: X.X±0.5 (X.XX±0.02)
X.XX±0.25 (X.XXX±0.01)
- ▶ Pin diameter tolerance: X.X±0.05 (X.XX±0.002)

Physical Characteristics

Case Size	: 31.8x20.3x12.0mm (1.25x0.80x0.47 inches)
Case Material	: Plastic resin (flammability to UL 94V-0 rated)
Pin Material	: Copper Alloy
Weight	: 15.5g


Recommended Pad Layout for Single & Dual Output Converter



Test Setup

Peak-to-Peak Output Noise Measurement Test

Refer to the output specifications or add 4.7µF capacitor if the output specifications undefine Cout. Scope measurement should be made by using a BNC socket, measurement bandwidth is 0-20 MHz. Position the load between 50 mm and 75 mm from the DC-DC Converter.



Technical Notes

Overload Protection


To provide hiccup mode protection in a fault (output overload) condition, the unit is equipped with internal current limiting circuitry and can endure overload for an unlimited duration.

Overvoltage Protection

The output overvoltage clamp consists of control circuitry, which is independent of the primary regulation loop, that monitors the voltage on the output terminals. The control loop of the clamp has a higher voltage set point than the primary loop. This provides a redundant voltage control that reduces the risk of output overvoltage. The OVP level can be found in the output data.


Input Source Impedance

The power module should be connected to a low ac-impedance input source. Highly inductive source impedances can affect the stability of the power module. In applications where power is supplied over long lines and output loading is high, it may be necessary to use a capacitor on the input to insure startup. By using a good quality low Equivalent Series Resistance (ESR < 1.0Ω at 100 kHz) capacitor of a 22µF for the 5V input devices and a 10µF for the 12V input devices and a 4.7µF for the 24V input devices and a 2.2µF for the 48V devices, capacitor mounted close to the power module helps ensure stability of the unit.



Output Ripple Reduction

A good quality low ESR capacitor placed as close as practicable across the load will give the best ripple and noise performance. To reduce output ripple, it is recommended to use 1µF capacitors at the output.




Maximum Capacitive Load

The MIW03M series has limitation of maximum connected capacitance on the output. The power module may operate in current limiting mode during start-up, affecting the ramp-up and the startup time. Connect capacitors at the point of load for best performance. The maximum capacitance can be found in the data sheet.

Thermal Considerations


Many conditions affect the thermal performance of the power module, such as orientation, airflow over the module and board spacing. To avoid exceeding the maximum temperature rating of the components inside the power module, the case temperature must be kept below 105°C. The derating curves are determined from measurements obtained in a test setup.



Packaging Information for Tube

Tube


Plug



Unit: mm
10 PCS per TUBE

Wave Soldering Considerations

Lead free wave solder profile



Zone	Reference Parameter
Preheat	Rise temp. speed : 3°C/sec max.
zone	Preheat temp. : 100~130°C
Actual	Peak temp. : 250~260°C
heating	Peak time(T1+T2) : 4~6 sec

Hand Welding Parameter

Reference Solder: Sn-Ag-Cu : Sn-Cu : Sn-Ag

Hand Welding: Soldering iron : Power 60W

Welding Time: 2~4 sec

Temp.: 380~400°C

Part Number Structure

M	I	W	03	-	05	S	05	M		
Package Type DIP-24		Wide 2:1 Input Voltage Range		Output Power 3.5 Watt		Input Voltage Range 05: 4.5 ~ 9 VDC 12: 9 ~ 18 VDC 24: 18 ~ 36 VDC 48: 36 ~ 75 VDC		Output Quantity S: Single D: Dual	Output Voltage 05: 5 VDC 058: 5.8 VDC 12: 12 VDC 15: 15 VDC	Application Medical

MTBF and Reliability

The MTBF of MIW03M series of DC-DC converters has been calculated using

MIL-HDBK 217F NOTICE2, Operating Temperature 25°C, Ground Benign.

Model	MTBF	Unit
MIW03-05S05M	5,815,448	Hours
MIW03-05S058M	5,815,624	
MIW03-05S12M	6,550,077	
MIW03-05S15M	6,469,133	
MIW03-05D12M	6,243,079	
MIW03-05D15M	6,125,684	
MIW03-12S05M	6,276,235	
MIW03-12S12M	6,935,581	
MIW03-12S15M	6,842,047	
MIW03-12D12M	6,599,533	
MIW03-12D15M	6,490,243	
MIW03-24S05M	6,277,101	
MIW03-24S12M	6,841,141	
MIW03-24S15M	6,842,430	
MIW03-24D12M	6,629,863	
MIW03-24D15M	6,411,241	
MIW03-48S05M	6,323,086	
MIW03-48S12M	6,715,023	
MIW03-48S15M	6,756,621	
MIW03-48D12M	6,445,972	
MIW03-48D15M	6,336,217	