


PRODUCT LINE PORTFOLIO

2023

POWER FOR
A BETTER FUTURE




SINCE 1990



ABOUT MINMAX

- In the three decades since MINMAX was established in 1990, we have prided ourselves on providing our customers with products and excellent service in a timely way. Our adherence to the best quality standards has also helped MINMAX win customers’ hearts and become a preferred business partner.
- “Power for a Better Future” We want MINMAX to be better than ever and to focus on the future. We hope MINMAX can work closely with all of our customers, materials suppliers, and employees. Our long-term partnership will help all of us move toward a brighter future, together.

OUR ADVANTAGES



CONTENTS

GENERAL INDUSTRIAL POWER SOLUTIONS

1-5W	SIP Package DC-DC Converters	05
1-6W	SMD Package DC-DC Converters	06
1-15W	DIP Package DC-DC Converters	07
10-30W	1"×1" Package DC-DC Converters	08
40-50W	2"×1" Package DC-DC Converters	08
6-60W	Chassis & DIN-Rail Mounting DC-DC Converters	09
0.5-1A	Switching Regulators	09
3-60W	Encapsulated Package AC-DC Power Supplies	10

RAILWAY CERTIFIED POWER SOLUTIONS

3 W	DIP Package DC-DC Converters	12
10-40 W	2"×1" Package DC-DC Converters	12
50-150 W	Quarter Brick DC-DC Converters	12

ULTRA-HIGH ISOLATION POWER SOLUTIONS

1-2W	SIP Package DC-DC Converters	14
1W	SMD Package DC-DC Converters	14
2-10W	DIP Package DC-DC Converters	14
15-20W	2"×1" Package DC-DC Converters	14
6-60W	Chassis & DIN-Rail Mounting DC-DC Converters	14

MEDICAL SAFETY POWER SOLUTIONS

1W	SIP Package DC-DC Converters	16
1-2W	SMD Package DC-DC Converters	16
2-10W	DIP Package DC-DC Converters	16
15-20W	2"×1" Package DC-DC Converters	16
24-60W	Encapsulated Package AC-DC Power Supplies	17

MINMAX POWER SOLUTIONS		18-19
------------------------	--	-------

[illegible]

Series	Output Power	Input Voltage Range (VDC)	Output Voltage (VDC)	Isolation (VDC)	Efficiency	Operating Ambient Temp. Range ⁽¹⁾	Output Regulation	No Min. Load	Package	OCp	SCP	Remote ON/OFF Control	UL/cUL/IEC/EN 60950-1	UL/cUL/IEC/EN 62368-1
MBU100	1W	2.97-3.63, 4.5-5.5, 10.8-13.2, 21.6-26.4	3.3, 5, 9, 12, 15	1000	80%	-40~+85°C			SIP-4					
MAU100	1W	4.5-5.5, 10.8-13.2, 13.5-16.5, 21.6-26.4	3.3, 5, 9, 12, 15, ±5, ±9, ±12, ±15	1000	81%	-40~+85°C			SIP-7				•	
MAU200	1W	4.5-5.5, 10.8-13.2, 21.6-26.4	3.3, 5, 9, 12, 15, ±5, ±9, ±12, ±15	3000	81%	-40~+90°C			SIP-7				•	
MAPU01H	1W	2.97-3.63, 4.5-5.5, 10.8-13.2, 21.6-26.4	3.3, 5, 9, 12, 15, ±5, ±12, ±15	3000	84%	-40~+90°C			SIP-7		•		•	•
MAW01	1W	4.5-9, 9-18, 18-36, 36-75	5, 12, 15, 24, ±12, ±15	1500	80%	-40~+95°C	•	•	SIP-6	•	•		•	•
MAPU02H	2W	4.5-5.5, 10.8-13.2, 21.6-26.4	3.3, 5, 9, 12, 15, ±5, ±12, ±15	3000	82%	-40~+90°C			SIP-7		•			
MCW1000	2W	4.5-9, 9-18, 18-36, 36-75	3.3, 5, 12	1000	81%	-40~+85°C	•		SIP-8	•	•	•	•	•
MCWI02	2W	4.5-18, 9-36, 18-75	3.3, 5, 12, 15, ±5, ±12, ±15	1500	82%	-40~+90°C	•	•	SIP-8	•	•	•	•	•
MBSU03	3W	4.5-5.5,10.8-13.2, 21.6-26.4	5, 12, 15	1500	86%	-40~+90°C			SIP-4		•			•
MCW03	3W	4.5-9, 9-18, 18-36,36-75	3.3, 5, 12, 15, ±5, ±12, ±15	1600	83%	-40~+85°C	•		SIP-8	•	•	•	•	•
MCWI03	3W	4.5-18, 9-36, 18-75	3.3, 5, 12, 15, ±5, ±12, ±15	1600	81%	-40~+85°C	•		SIP-8	•	•	•	•	•
MCW04	4W	9-18, 18-36, 36-75	5, 12, 15, 24, ±12, ±15	1600	87%	-40~+85°C	•	•	SIP-8	•	•	•		•
MCWI04	4W	9-36, 18-75	5, 12, 15, 24, ±12, ±15	1600	83%	-40~+85°C	•	•	SIP-8	•	•	•	•	•
MCWI05	5W	4.5-18, 9-36, 18-75	3.3, 5, 12, 15, 24, ±12, ±15	1500	84%	-40~+75°C	•	•	SIP-8	•	•	•	•	•

⁽¹⁾ Please refer to derating curve information from datasheet

GENERAL INDUSTRIAL • DC-DC CONVERTERS



1-6W SMD PACKAGE



Series	Output Power	Input Voltage Range (VDC)	Output Voltage (VDC)	Isolation (VDC)	Efficiency	Operating Ambient Temp. Range ⁽¹⁾	Output Regulation	No Min. Load	OCP	SCP	Remote ON/OFF Control	Water-washable Process Available	UL/cUL/IEC/EN 60950-1	UL/cUL/IEC/EN 62368-1
MSLU100	1W	4.5-5.5, 10.8-13.2, 13.5-16.5, 21.6-26.4	3.3, 5, 9, 12, 15, ±5, ±12, ±15	1500	80%	-40~+90°C						•	•	•
MSLU300	1W	4.5-5.5, 10.8-13.2, 21.6-26.4	3.3, 5, 12, 15, ±5, ±12, ±15	3000	81%	-40~+90°C						•		
MSPU01H	1W	2.97-3.63, 4.5-5.5, 10.8-13.2	3.3, 5, 12, 15, ±5, ±12, ±15	3000	85%	-40~+85°C			•	•		•	•	•
MSCW01	1W	4.5-9, 9-18, 18-36, 36-75	5, 12, 15, ±12, ±15	1500	82%	-40~+85°C	•	•	•	•	•	•	•	•
MSLU400	2W	4.5-5.5, 10.8-13.2, 21.6-26.4	3.3, 5, 12, ±5, ±12, ±15	1500	80%	-40~+92.5°C						•		
MSDW1000	2W	4.5-9, 9-18, 18-36, 36-75	3.3, 5, 12, 15, ±5, ±12, ±15	1500	81%	-40~+85°C	•		•			•	•	
MSCWI02	2W	4.5-12, 9-36, 18-75	5, 12, 15, 24, ±12, ±15	1500	85%	-40~+80°C	•	•	•	•	•	•	•	•
MSCWI03	3W	4.5-12, 9-36, 18-75	5, 12, 15, 24, ±12, ±15	1500	85%	-40~+80°C	•	•	•	•	•	•	•	•
MSGWI06	6W	9-36, 18-75	3.3, 5, 12, 15, 24 ±5, ±12, ±15	1500	83%	-40~+80°C	•		•	•	•	•	•	•

* Qualified to IPC/JEDEC J-STD-020D.1
* Tape & Reel Package Available
⁽¹⁾ Please refer to derating curve information from datasheet

GENERAL INDUSTRIAL • DC-DC CONVERTERS



1-15W DIP PACKAGE



Series	Output Power	Input Voltage Range (VDC)	Output Voltage (VDC)	Isolation (VDC)	Efficiency	Operating Ambient Temp. Range ⁽¹⁾	Output Regulation	No Min. Load	Package	OCP/SCP	Remote ON/OFF Control	UL/cUL/IEC/EN 62368-1
MFSU01	1W	4.5-5.5, 10.8-13.2, 21.6-26.4	5, 12, 15	1500	83%	-40~+85°C			DIP-8	SCP		
MFPU01H	1W	2.97-3.63, 4.5-5.5, 10.8-13.2	3.3, 5, 12, 15, ±5, ±12, ±15	3000	83%	-40~+90°C			DIP-8	•		•
MFW02	2W	4.5-10, 9-18, 18-36, 36-75	3.3, 5, 12, 15, ±5, ±12, ±15	1500	87%	-40~+80°C	•	•	DIP-8	•		•
MFW03	3W	4.5-10, 9-18, 18-36, 36-75	3.3, 5, 12, 15, ±5, ±12, ±15	1500	87%	-40~+80°C	•	•	DIP-8	•		•
MDWI03	3W	9-36, 18-75	3.3, 5, 12, 15, 24, ±5, ±12, ±15	1500	80%	-40~+85°C	•		DIP-16	•	•	•
MIW03	3W	4.5-9, 9-18, 18-36, 36-75	3.3, 5, 12, 15, 24, ±5, ±12, ±15	1500 3000	85%	-40~+85°C	•	•	DIP-24	•		•
MIWI03	3W	9-36, 18-75	3.3, 5, 12, 15, 24, ±5, ±12, ±15	1500 3000	84%	-40~+85°C	•	•	DIP-24	•		•
MIW06	6W	9-18, 18-36, 36-75	3.3, 5, 12, 15, 24, ±5, ±12, ±15	1500 3000	84%	-40~+85°C	•	•	DIP-24	•		
MIWI06	6W	9-36, 18-75	3.3, 5, 12, 15, 24, ±5, ±12, ±15	1500 3000	84%	-40~+85°C	•	•	DIP-24	•		•
MDWI06	6W	9-36, 18-75	3.3, 5, 12, 15, 24, ±5, ±12, ±15	1500	87%	-40~+90°C	•	•	DIP-16	•		•
MDW08	8W	9-18, 18-36, 36-75	3.3, 5, 12, 15, 24, ±12, ±15	1500	86%	-40~+80°C	•	•	DIP-16	•		•
MDWI08	8W	9-36, 18-75	3.3, 5, 12, 15, 24, ±12, ±15	1500	86%	-40~+80°C	•	•	DIP-16	•		•
MDW10	10W	9-18, 18-36, 36-75	3.3, 5, 5.1, 12, 15, 24, ±12, ±15	1500	88%	-40~+88°C	•	•	DIP-16	•		•
MDWI10	10W	9-36, 18-75	3.3, 5, 5.1, 12, 15, 24, ±12, ±15	1500	88%	-40~+88°C	•	•	DIP-16	•		•
MIW10	10W	9-18, 18-36, 36-75	3.3, 5, 5.1, 12, 15, ±12, ±15	1500	89%	-40~+85°C	•	•	DIP-24	•	•	•
MIWI10	10W	9-36, 18-75	3.3, 5, 5.1, 12, 15, 24, ±12, ±15	1500	87%	-40~+85°C	•	•	DIP-24	•	•	•
NEW MDW12	12W	9-18, 18-36, 36-75	5, 5.1, 12, 15, 24, ±12, ±15	1500	88%	-40~+85°C	•	•	DIP-16	•		•
NEW MDWI12	12W	9-36, 18-75	5, 5.1, 12, 15, 24, ±12, ±15	1500	88%	-40~+85°C	•	•	DIP-16	•		•
NEW MDW15	15W	9-18, 18-36, 36-75	5.1, 12, 15, 24, ±12, ±15	1500	87%	-40~+85°C	•	•	DIP-16	•		•
NEW MDWI15	15W	9-36, 18-75	5.1, 12, 15, 24, ±12, ±15	1500	87%	-40~+85°C	•	•	DIP-16	•		•

⁽¹⁾ Please refer to derating curve information from datasheet

GENERAL INDUSTRIAL • DC-DC CONVERTERS



10-30W 1" x 1" PACKAGE



Series	Output Power	Input Voltage Range (VDC)	Output Voltage (VDC)	Isolation (VDC)	Efficiency	Operating Ambient Temp. Range ⁽¹⁾	Output Regulation	No Min. Load	OCP/SCP	OVD	Remote ON/OFF Control	Output Voltage Trim	UL/cUL/IEC/EN 62368-1
MJW10	10W	9-18, 18-36, 36-75	3.3, 5, 5.1, 12, 15, ±5, ±12, ±15	1500	89%	-40~+80°C	•	•	•		•		•
MJW110	10W	9-36, 18-75	3.3, 5, 5.1, 12, 15, 24, ±5, ±12, ±15	1500	87%	-40~+80°C	•		•		•		•
MJW15	15W	9-18, 18-36, 36-75	3.3, 5, 12, 15, 24, ±12, ±15	1500	91%	-40~+90°C	•	•	•	•	•	•	•
MJW115	15W	9-36, 18-75	3.3, 5, 12, 15, 24, ±12, ±15	1500	91%	-40~+90°C	•	•	•	•	•	•	•
MJW120	20W	9-36, 18-75	3.3, 5, 12, 15, 24, ±12, ±15	1500	89%	-40~+85°C	•	•	•	•	•	•	•
MJW25	25W	9-18, 18-36, 36-75	3.3, 5, 12, 15, ±12, ±15	1500	90%	-40~+80°C	•	•	•	•	•	•	•
MJW125	25W	9-36, 18-75	3.3, 5, 12, 15, ±12, ±15	1500	90%	-40~+80°C	•	•	•	•	•	•	•
NEW MJW130	30W	9-36, 18-75	3.3, 5, 12, 15, 24, ±12, ±15	1500	90%	-40~+80°C	•	•	•	•	•	•	•



40-50W 2" x 1" PACKAGE



Series	Output Power	Input Voltage Range (VDC)	Output Voltage (VDC)	Isolation (VDC)	Efficiency	Operating Ambient Temp. Range ⁽¹⁾	Output Regulation	No Min. Load	Package	OCP/SCP	OVP/OTP	Remote ON/OFF Control	Output Voltage Trim	UL/cUL/IEC/EN 60950-1	UL/cUL/IEC/EN 62368-1
MKW40	40W	9-18, 18-36, 36-75	3.3, 5, 12, 15, 24 ±12, ±15	1500	92%	-40~+80°C	•	•	2" x 1"	•	•	•	•	•	•
MKW140	40W	9-36, 18-75	3.3, 5, 12, 15, 24 ±12, ±15	1500	91%	-40~+80°C	•	•	2" x 1"	•	•	•	•	•	•
MKW50	50W	9-18, 18-36, 36-75	3.3, 5, 12, 15, 24	1500	92%	-40~+80°C	•	•	2" x 1"	•	•	•	•	•	•
MKW150	50W	9-36, 18-75	3.3, 5, 12, 15, 24	1500	92%	-40~+80°C	•	•	2" x 1"	•	•	•	•	•	•

⁽¹⁾ Please refer to derating curve information from datasheet

GENERAL INDUSTRIAL • DC-DC CONVERTERS



6-60W CHASSIS & DIN-RAIL MOUNTING



Series	Output Power	Input Voltage Range (VDC)	Output Voltage (VDC)	Isolation (VDC)	Efficiency	Operating Ambient Temp. Range ⁽¹⁾	Output Regulation	No Min. Load	Package	OCP/SCP	OVP	Remote ON/OFF Control	UL/cUL/IEC/EN 62368-1
MJWI06C	6W	9-36, 18-75	5, 5.1, 12, 15, 24, 48, ±12, ±15, ±24	3000VDC	85%	-40~+92.5°C	•	•	Chassis DIN-Rail	•		•	•
MKWI10C	10W	9-36, 18-75	5, 5.1, 12, 15, 24, 48, ±12, ±15, ±24	3000VDC	86%	-40~+92.5°C	•	•	Chassis DIN-Rail	•		•	•
MOWI20C	20W	9-36, 18-75	5.1, 12, 24, 48	2500VDC	91%	-40~+90°C	•	•	Chassis DIN-Rail	•	•	•	•
MQWI40C	40W	9-36, 18-75	5.1, 12, 24, 48	2500VDC	92%	-40~+85°C	•	•	Chassis DIN-Rail	•	•	•	•
MRWI60C	60W	9-36, 18-75	5.1, 12, 24, 48	2500VDC	92%	-40~+85°C	•	•	Chassis DIN-Rail	•	•	•	•



0.5-1A SWITCHING REGULATORS



Series	Output Power	Input Voltage Range (VDC)	Output Voltage (VDC)	Efficiency	Operating Ambient Temp. Range ⁽¹⁾	Output Regulation	No Min. Load	Package	OTP	SCP	Remote ON/OFF Control	UL/cUL/IEC/EN 62368-1
M78AR-0.5	0.5A	4.75-32	1.5, 1.8, 2.5, 3.3	91%	-40~+90°C	•	•	SIP-3	•	•		
		6.5- 32	5	94%	-40~+90°C	•	•	SIP-3	•	•		
		8-32	6.5	95%	-40~+90°C	•	•	SIP-3	•	•		
		11-32	9	96%	-40~+90°C	•	•	SIP-3	•	•		
		15-32	12	97%	-40~+90°C	•	•	SIP-3	•	•		
		18-32	15	97%	-40~+90°C	•	•	SIP-3	•	•		
M78SAR-0.5	0.5A	4.75-32	1.5, 1.8, 2.5, 3.3	91%	-40~+90°C	•	•	SMD	•	•	•	•
		6.5-32	5	94%	-40~+90°C	•	•	SMD	•	•	•	•
		8-32	6.5	95%	-40~+90°C	•	•	SMD	•	•	•	•
		11-32	9	96%	-40~+90°C	•	•	SMD	•	•	•	•
		15-32	12	97%	-40~+90°C	•	•	SMD	•	•	•	•
		18-32	15	97%	-40~+90°C	•	•	SMD	•	•	•	•
M78AR-1	1A	6.5-32	3.3	93%	-40~+85°C	•	•	SIP-3	•	•		
		6.5-32	5	94%	-40~+85°C	•	•	SIP-3	•	•		
		15-32	12	96%	-40~+85°C	•	•	SIP-3	•	•		

⁽¹⁾ Please refer to derating curve information from datasheet

GENERAL INDUSTRIAL • AC-DC POWER SUPPLIES



3-60W ENCAPSULATED PACKAGE



Series	Output Power	Input Voltage Range	Output Voltage (VDC)	Isolation (VDC)	Efficiency	Operating Ambient Temp. Range ⁽¹⁾	Output Regulation	No Min. Load	Package	Case Size (inches)	SCP/OCP/OVP	UL/cUL/IEC/EN 62368-1	UL/cUL/IEC/EN 60335-1
AAF-03	3W	85 – 264VAC 120-370VDC	3.3, 5, 9, 12, 15, 24	3000 VAC Reinforced	78%	-25~+70°C	• •	•	PCB	1.00x1.00x0.64"	•	•	•
ABF-04	4W	85 – 264VAC 120-370VDC	3.3, 5, 9, 12, 15, 24, 5/3.3, 12/5, ±12, ±15	3000 VAC Reinforced	77%	-25~+60°C	• •	•	PCB	1.44x1.06x0.67"	•	•	•
AAF-05	5W	85 – 264VAC 120-370VDC	3.3, 5, 9, 12, 15, 24, 48	3000 VAC Reinforced	85%	-25~+70°C	• •	•	PCB Chassis	1.00x1.00x0.64" 1.65x1.02x0.76"	•	•	•
NEW AMF-07	7W	85 – 264VAC 90-370VDC	5, 12, 15, 24, 48	3000 VAC Reinforced	85%	-40~+80°C	•	•	PCB Chassis	1.52x1.0x0.66" 2.40x1.20x0.74"	•	•	•
ACF-10	10W	85 – 264VAC 120-370VDC	3.3, 5, 12, 15, 24, 48	4000 VAC Reinforced	86%	-25~+70°C	• •	•	PCB	1.52x1.00x0.62"	•	•	•
NEW AGF-15	15W	85 – 264VAC 120-370VDC	3.3, 5, 9, 12, 15, 24, 48	3000 VAC Reinforced	84%	-25~+70°C	• •	•	PCB	2.06x1.07x0.93	•	•	•
NEW AMF-15	15W	85 – 264VAC 90-370VDC	5.1, 12, 15, 24, 48	3000 VAC Reinforced	86%	-40~+70°C	• •	•	PCB Chassis & DIN-Rail	2.06x1.07x0.93" 2.89x1.18x0.91"	•	•	•
NEW AMF-30	30W	85 – 264VAC 90-370VDC	5.1, 12, 15, 24, 48	3000 VAC Reinforced	88%	-40~+70°C	• •	•	PCB Chassis & DIN-Rail	2.52x1.77x0.94" 3.39x1.15x1.00"	•	•	•
NEW AMF-60	60W	85 – 264VAC 90-370VDC	5.1, 12, 15, 24, 48	3000 VAC Reinforced	89%	-40~+70°C	• •	•	PCB Chassis & DIN-Rail	2.99x2.13x1.10" 3.86x2.20x1.12"	•	•	•

⁽¹⁾ Please refer to derating curve information from datasheet

MINMAX TECHNOLOGY



RAILWAY CERTIFIED
POWER SOLUTIONS

MINMAX TECHNOLOGY

RAILWAY CERTIFIED • DC-DC CONVERTERS



3-150W • DIP • 2"x1" PACKAGE • QUARTER BRICK



Series	Output Power	Input Voltage Range (VDC)	Output Voltage (VDC)	Isolation (VAC)	Efficiency	Operating Ambient Temp. Range ⁽¹⁾	No Min. Load	OC/SCP	OVP	OTP	Remote ON/OFF Control	Output Voltage Trim	Output Sense	EN50155 (IEC60571)	UL/cUL/IEC/EN 62368-1
3W • DIP Package															
MIZI03	3W	9-36 18-75 40-160	5, 12, 15, ±12, ±15	3000VAC Reinforced	85%	-40~+92°C Ambient	•	•						•	•
10-40W • 2"x1" Package															
MKZI10	10W	9-36 18-75 40-160	5, 12, 15, 24, ±12, ±15	3000VAC Reinforced	89%	-40~+95°C Ambient	•	•	•		•	•		•	•
MKZI20	20W	9-36 18-75 40-160	5, 12, 15, 24, ±12, ±15	3000VAC Reinforced	88%	-40~+88.5°C Ambient	•	•	•		•	•		•	•
NEW MKZI40	40W	36-160	5, 12, 15, 24, ±12, ±15	3000VAC Reinforced	90%	-40~+77.5°C Ambient	•	•	•	•	•	•		•	•
50-150W • Quarter Brick															
MTQZ50	50W	43-101 66-160	5, 12, 15, 24	3000VAC Reinforced	92%	-40~+85°C Ambient	•	•	•	•	•	•	•	•	•
NEW MRZI75	75W	36-160 ⁽²⁾	5, 12, 15, 24, 54	2000VAC Reinforced	91%	-40~+105°C Base plate	•	•	•	•	•	•	•	•	•
NEW MRZI100	100W	36-160 ⁽²⁾	5, 12, 15, 24, 54	2000VAC Reinforced	91.5%	-40~+105°C Base plate	•	•	•	•	•	•	•	•	•
NEW MRZI150	150W	36-160 ⁽²⁾	5, 12, 15, 24, 54	2000VAC Reinforced	90%	-40~+105°C Base plate	•	•	•	•	•	•	•	•	•

⁽¹⁾Please refer to derating curve information from datasheet
⁽²⁾Please refer to star-up voltage information from datasheet

MINMAX TECHNOLOGY



ULTRA-HIGH ISOLATION
POWER SOLUTIONS

Input

Isolation
5K VAC / 60sec

Output

Reinforced Insulation

MINMAX TECHNOLOGY

ULTRA-HIGH ISOLATION • DC-DC CONVERTERS



1-60W • SIP • SMD • DIP • 2"×1" CHASSIS & DIN-RAIL PACKAGE



Series	Output Power	Input Voltage Range (VDC)	Output Voltage (VDC)	Isolation	Working Voltage	Efficiency	Operating Ambient Temp. Range ⁽¹⁾	Output Regulation	No Min. Load	OCP	OVP	SCP	UL/cUL/IEC/EN 62368-1
1-2W • SIP Package													
MA01-HI	1W	4.5-5.5, 10.8-13.2, 13.5-16.5, 21.6-26.4	3.3, 5, 9, 12, 15, ±5, ±9, ±12, ±15, ±15/-9	5200VDC		80%	-40~+90°C					•	•
MAEU01-HI	1W	4.5-5.5, 10.8-13.2, 21.6-26.4	5, 12, 15	3000VAC Reinforced	480 Vrms	81%	-40~+95°C					•	•
MAEU02-HI	2W	4.5-5.5, 10.8-13.2, 13.5-16.5, 21.6-26.4	3.3, 5, 9, 12, 15, ±5, ±9, ±12, ±15, ±15/-9	5200VDC		85%	-40~+85°C					•	•
1W • SMD Package													
MSCEU01-HI	1W	4.5-5.5, 10.8-13.2, 21.6-26.4	5, 12, 15, ±12, ±15	3000VAC Reinforced	480 Vrms	84%	-40~+95°C					•	•
2-10W • DIP Package													
MDEU02-HI	2W	4.5-5.5, 10.8-13.2, 21.6-26.4	5, 12, 15, ±12, ±15	4000VAC Reinforced	300 Vrms	75%	-25~+80°C					•	•
MIE03-HI	3.5W	4.5-9, 9-18, 18-36, 36-75	5, 5.8, 12, 15, 24, ±12, ±15	5000VAC Reinforced	1000 Vrms	87%	-40~+96°C	•	•	•	•	•	•
MIE06-HI	6W	9-18, 18-36, 36-75	5, 12, 15, 24, ±12, ±15	5000VAC Reinforced	1000 Vrms	89%	-40~+95°C	•	•	•	•	•	•
MIE10-HI	10w	9-18, 18-36, 36-75	3.3, 5, 5.1, 12, 15, 24, ±12, ±15	5000VAC Reinforced	1000 Vrms	88%	-40~+90°C	•	•	•	•	•	•
15-20W • 2"×1" Package													
MKE15-HI	15W	9-18, 18-36, 36-75	5, 5.1, 12, 15, 24, ±12, ±15	4200VAC Reinforced	1000 Vrms	90%	-40~+85°C	•	•	•	•	•	•
MKE20-HI	20W	9-18, 18-36, 36-75	5, 5.1, 12, 15, 24, ±12, ±15	4200VAC Reinforced	1000 Vrms	90%	-40~+80°C	•	•	•	•	•	•
6-60W • Chassis & DIN-Rail Mounting													
MJA06C	6W	80-160	5, 5.1, 12, 15, 24, 48, ±12, ±15, ±24	3000VAC Reinforced	1000 Vrms	84%	-40~+92.5°C	•	•	•	•		•
MKA10C	10W	80-160	5, 5.1, 12, 15, 24, 48, ±12, ±15, ±24	3000VAC Reinforced	1000 Vrms	85%	-40~+87°C	•	•	•	•		•
MOA20C	20W	80-160	5, 5.1, 12, 15, 24, 48, ±12, ±15, ±24	3000VAC Reinforced	1000 Vrms	88%	-40~+94.5°C	•	•	•	•	•	•
MQA40C	40W	80-160	5, 5.1, 12, 15, 24, 48, ±12, ±15, ±24	3000VAC Reinforced	1000 Vrms	89%	-40~+90°C	•	•	•	•	•	•
MRA60C	60W	80-160	5, 5.1, 12, 15, 24, 48, ±12, ±15, ±24	3000VAC Reinforced	1000 Vrms	89%	-40~+90.5°C	•	•	•	•	•	•

⁽¹⁾Please refer to derating curve information from datasheet

MEDICAL SAFETY
POWER SOLUTIONS

IEC 60601-1 APPROVED

2 X MOPP

MINIMAX TECHNOLOGY

Medical Safety • DC-DC Converters



1-20W • SIP • SMD • DIP • 2"×1" PACKAGE



Series	Output Power	Input Voltage Range (VDC)	Output Voltage (VDC)	Isolation (VAC)	Efficiency	Operating Ambient Temp. Range ⁽¹⁾	Output Regulation	No Min. Load	OCP	OVP	SCP	Protection Level	ANSI/AAMI ES 60601-1	IEC/EN 60601-1 3 rd
1W • SIP Package														
MAU400	1W	4.5-5.5, 10.8-13.2	5, 12, 15, ±5, ±12, ±15	3000VAC Reinforced	75%	-25~+85°C						1xMOPP 2xMOOP	•	•
MAU01M	1W	4.5-5.5, 10.8-13.2, 21.6-26.4	5, 12, 15	4000VAC Reinforced	81%	-40~+95°C					•	2xMOPP	•	•
1-2W • SMD Package														
MSCU01M	1W	4.5-5.5, 10.8-13.2, 21.6-26.4	5, 12, 15, ±12, ±15	4000VAC Reinforced	84%	-40~+95°C					•	2xMOPP	•	•
MSHU100	2W	4.5-5.5, 10.8-13.2, 21.6-26.4	5, 12, 15, ±12, ±15	4000VAC Reinforced	75%	-25~+80°C						1xMOPP 2xMOOP	•	•
2-10W • DIP Package														
MDHU100	2W	4.5-5.5, 10.8-13.2, 21.6-26.4	5, 12, 15, ±12, ±15	4000VAC Reinforced	75%	-25~+80°C						1xMOPP 2xMOOP	•	•
MIHW2000	3W	9-40, 18-80, 36-160	5, 12, 15, ±12, ±15	4000VAC Reinforced	83%	-40~+85°	•		•		•	1xMOPP 2xMOOP	•	•
MIW03M	3.5W	4.5-9, 9-18, 18-36, 36-75	5, 5.8, 12, 15, ±12, ±15	5000VAC Reinforced	87%	-40~+96°C	•	•	•	•	•	2xMOPP	•	•
MIW06M	6W	9-18, 18-36, 36-75	5, 12, 15, ±12, ±15	5000VAC Reinforced	89%	-40~+95°C	•	•	•	•	•	2xMOPP	•	•
MIW10M	10W	9-18, 18-36, 36-75	3.3, 5, 5.1, 12, 15, 24, ±12, ±15	5000VAC Reinforced	88%	-40~+90°C	•	•	•	•	•	2xMOPP	•	•
15-20W • 2"×1" Package														
MKW15M	15W	9-18, 18-36, 36-75	5, 5.1, 12, 15, 24, ±12, ±15	4200VAC Reinforced	90%	-40~+85°C	•	•	•	•	•	2xMOPP	•	•
MKW20M	20W	9-18, 18-36, 36-75	5, 5.1, 12, 15, 24, ±12, ±15	4200VAC Reinforced	90%	-40~+80°C	•	•	•	•	•	2xMOPP	•	•

⁽¹⁾ Please refer to derating curve information from datasheet

Medical Safety • AC-DC POWER SUPPLIES



24-60W • ENCAPSULATED PACKAGE



Series	Output Power	Input Voltage Range (VAC)	Output Voltage (VDC)	Isolation (VAC)	Efficiency	Operating Ambient Temp. Range ⁽¹⁾	Output Regulation	No Min. Load	Package	OCP/SCP	OVP	Protection Level	ANSI/AAMI ES 60601-1	IEC/EN 60601-1 3 rd
AJM-24	24W	85-264	5, 9, 12, 15, 24, ±12 ±15	4000VAC Reinforced	85%	-40~+80°C	•	•	PCB Chassis DIN-Rail	•	•	2xMOPP	•	•
APM-40	40W	85-264	5, 12, 15, 24, ±12 ±15	4000VAC Reinforced	85%	-40~+80°C	•	•	PCB Chassis DIN-Rail	•	•	2xMOPP	•	•
AYM-60	60W	85-264	5.1, 12, 15, 24, 48	4000VAC Reinforced	85%	-40~+80°C	•	•	PCB Chassis DIN-Rail	•	•	2xMOPP	•	•

⁽¹⁾ Please refer to derating curve information from datasheet

MINMAX POWER SOLUTIONS
DC-DC CONVERTERS · AC-DC POWER SUPPLIES | 1-150W



GENERAL INDUSTRIAL

• DC-DC CONVERTERS

SIP Package

1-5W

SMD Package

1-6W

DIP Package

1-15W

Encapsulated Package

3-60W

1"x1" Package

10-30W


2"x1" Package

40-50W

Chassis & DIN-Rail Mounting

6-60W

• AC-DC POWER SUPPLIES



RAILWAY CERTIFIED

• DC-DC CONVERTERS

DIP Package

3W


2"x1" Package

10-40W

Quarter Brick

50-150W

MINMAX POWER SOLUTIONS
DC-DC CONVERTERS · AC-DC POWER SUPPLIES | 1-150W



ULTRA-HIGH ISOLATION

• DC-DC CONVERTERS

SIP Package

1-2W

SMD Package

1W

DIP Package

2-10W

2"x1" Package

15-20W

Chassis & DIN-Rail Mounting

6-60W



MEDICAL SAFETY

• DC-DC CONVERTERS

SIP Package

1W

SMD Package

1-2W

Encapsulated Package

24-60W

DIP Package

2-10W



2"x1" Package

15-20W

• AC-DC POWER SUPPLIES

**POWER FOR
A BETTER FUTURE**

FOR MORE INFO, PLEASE GO TO  www.minimaxpower.com



ADDRESS
No.18,Sin Sin Rd.,An-ping
Industrial Dist., Tainan702 Taiwan

MAIL
sales@minmax.com.tw

TELEPHONE
(+886) 6-2923150

FAX
(+886) 6-2923149



MINMAX TECHNOLOGY CO., LTD.